

FLOOR, WALL & MOSAIC

BELMAR™
GLAZED CERAMIC



Photo features Belmar Pewter 18 x 18 on the floor.

Never before has rustic charm met sophistication quite like Belmar™. Its vivid stone texture complements the rich collection of color and design options providing the unique opportunity to create a cohesive contemporary design. Coordinating wall and mosaic tile elements offer limitless style and design opportunities for a cohesive living space. A wide size assortment reflects distinguished aesthetics. Belmar is available in a rich palette of shades and two attractive mosaic options.

GLAZED CERAMIC FLOOR TILE



PEARL BL90



CASHMERE BL91



PEWTER BL93



TORTOISE BL94



OLIVE BL92

GLAZED CERAMIC WALL TILE



PEARL BL90



CASHMERE BL91



TORTOISE BL94

GLAZED CERAMIC MOSAIC



CREAM BLEND BL95
(Pearl, Cashmere, Tortoise)



EARTH BLEND BL96
(Olive, Tortoise, Pewter)



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

FLOOR, WALL & MOSAIC



Photo features Belmar™ Tortoise 12 x 12 on the floor and 3 x 6 on the wall.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	18 x 18 Floor Tile	17-11/16" x 17-11/16" (45.01 cm x 45.01 cm)	5/16"	17.44	8
	12 x 12 Floor Tile	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"	15.52	16
	9 x 12 Wall Tile †	8-15/16" x 11-15/16" (22.70 cm x 30.30 cm)	5/16"	11.25	15
	6 x 6 Wall Tile †	6" x 6" (15.20 cm x 15.20 cm)	5/16"	12.50	50
	3 x 6 Wall Tile †	3" x 6" (7.60 cm x 15.20 cm)	5/16"	12.50	100
	2 x 2 Mosaic ■	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12
	4 x 12 Floor/Wall Accent	3-7/8" x 12-3/8" (9.84 cm x 31.43 cm)	5/16"	- -	10

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P-43C9	22
	Wall Bullnose (9" side)	3 x 9	S-4309	54
	Wall Bullnose Outcorner	3 x 3	SN-4309	32
	Wall Bullnose	6 x 6	S-4669	50
	Wall Bullnose Outcorner	6 x 6	SCRL-4669	50
	Wall Bullnose (6" side)	2 x 6	S-4269	100
	Wall Bullnose Outcorner	2 x 2	SN-4269	25
	Radius Bullnose	2 x 6	A-4200	100
	Radius Bullnose Outcorner	2 x 2	AN-4200	200
	Mosaic Bullnose	2 x 2	S-886	108
	Counter Rail	2 x 6	26-CRWL	36
	Counter Rail Corner	2 x 2	22-CRCN	24
	Quarter Round	1 x 6	A-106	152
	Quarter Round Outcorner	1 x 1	UC-106	40

† Wall tile and trim available in BL90, BL91 and BL94 only ■ Dot-mounted

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:


Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length of 15" or greater in a staggered brick-joint pattern.)

Wall: 1/16"

Mosaic: 1/8"

RELATIVE PRICING: Medium

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs.	120 - 230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	4	N/A	4

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●*
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors (Residential or Light Commercial)	≥ 0.42	●**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●***
Pool Linings	N/A	●****

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Wall tile not suitable for this application

** Mosaic tile only

*** Floor, mosaic, 6 x 6 and 3 x 6 wall tile only

**** Mosaic, 6 x 6 and 3 x 6 wall tile only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.