

FLOOR

BORDEAUX™
GLAZED PORCELAIN



Photo features Bordeaux Chameau 20 x 20, 13 x 20, 13 x 13 and 6-1/2 x 6-1/2 on the floor.

BORDEAUX™ GLAZED PORCELAIN FLOOR WITH REVEAL IMAGING®

Distinctive detailing offered in a variety of sizes make this modular floor tile the product of choice for design versatility. Add coordinating glazed ceramic decorative accents for a timeless design.

BORDEAUX™

GLAZED PORCELAIN FLOOR TILE



CRÈME BD01



CHAMEAU BD02



MARRON BD03

DECORATIVE ACCENTS








UNIVERSAL BD99
Floor Accent



Photo features Bordeaux™ Chameau 20 x 20, 13 x 20, 13 x 13 and 6-1/2 x 6-1/2 on the floor.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	20 x 20 Floor Tile *	19-3/4" x 19-3/4" (50.20 cm x 50.20 cm)	5/16"	16.27	6
	13 x 20 Floor Tile *	13-1/8" x 19-3/4" (33.30 cm x 50.20 cm)	5/16"	12.86	7
	13 x 13 Floor Tile *	13-1/8" x 13-1/8" (33.30 cm x 33.30 cm)	5/16"	16.72	14
	6-1/2 x 6-1/2 Floor Tile *	6-7/16" x 6-7/16" (16.40 cm x 16.40 cm)	5/16"	15.63	54
	3 x 13 Floor Accent □	3" x 13-1/8" (7.60 cm x 33.30 cm)	5/16"	- -	8

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose		3 x 13	P-43E9 30

* Modular sizes □ Ceramic body

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)

RELATIVE PRICING: Medium

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	4

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	●*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	●*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

* 6-1/2 x 6-1/2 floor tile only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.