

WALL

BRIGHT & MATTE™
GLAZED CERAMIC



Photo features Bright & Matte Pomegranate 4-1/4 x 4-1/4 and Satinbrites™ Almond 2 x 2 mosaic on the wall.

BRIGHT & MATTE™ GLAZED CERAMIC WALL



The Bright and Matte™ collections offer a spectrum of colors from neutral tones to vivid hues. Choose between a high-gloss or smooth satin finish for backsplash designs and statement walls, or create a custom effect when you coordinate Bright and Matte together.

BRIGHT & MATTE™

BRIGHT

							
ICE WHITE 0025 (1) ◆	WHITE 0090 (1)	BISCUIT 0091 (1) ◆	SALT & PEPPER 0045 (1)	GLOSS ALMOND 0012 (1)	CAPPUCCINO 0078 (1)	MUSHROOM 0038 (2)	NUTMEG 0037 (2)
							
SAND DOLLAR 0050 (1)	MARSHMALLOW 0065 (1)	LEMON CHIFFON 0044 (1)	CHILI PEPPER Q074 (4) ✦	ANTIQUE ROSE Q073 (4) ✦	POMEGRANATE Q072 (4) ✦	ARTICHOKE 0063 (1) ●	DILL PICKLE 0083 (2) ●
							
SUMMER RAIN 0081 (1)	SAPPHIRE SKY 0070 (3) ●	LIGHT SMOKE 0042 (1)	STORM GRAY 0040 (2)	SMOKEY QUARTZ 0047 (2) ●	GLOSS BLACK 0049 (2) ◆		
							
LEMON ZEST Q075 (4) ✦	MANDARIN ORANGE Q077 (4) ✦	WATERMELON SORBET Q070 (4) ✦	GREEN APPLE Q076 (4) ✦	SHAMROCK GREEN Q078 (4) ✦	PEACOCK BLUE Q084 (4) ✦	RUBY RED 0121 (5) ◆	GRAPE SODA Q079 (4) ✦ ◆

MATTE

							
MATTE DESIGNER WHITE 0061 (1) ◆	MATTE SNOW MIST 0095 (1)	MATTE BISCUIT 0092 (1) ◆	MATTE ALMOND 0087 (1)	MATTE CAPPUCCINO 0009 (1)	MATTE MUSHROOM 0041 (2)	MATTE NUTMEG 0039 (2)	MATTE SAND DOLLAR 0067 (1)
							
MATTE ARTICHOKE 0069 (1) ●	MATTE DILL PICKLE 0066 (2) ●	MATTE GLACIER 0062 (1)	MATTE BIMINI BLUE 0085 (2) ●	MATTE LIGHT SMOKE 0004 (1)	MATTE SMOKEY QUARTZ 0028 (2) ●	MATTE BLACK 0064 (2) ◆	

(1), (2), (3), (4) & (5) notations indicate price group, (1) being the least expensive.

- ◆ Available in chair rail
- ✦ These colors are special order and requires 1-2 weeks for delivery from date of order.
- ◆ Subject to crazing, do not use black grout.
- These colors are made to order and requires 6-8 weeks for delivery from date of order.





All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.




























BRIGHT & MATTE™ GLAZED CERAMIC WALL

WALL

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	6 x 6 Wall Tile	6" x 6" (15.20 cm x 15.20 cm)	5/16"	12.50	50
	4-1/4 x 4-1/4 Wall Tile	4-1/4" x 4-1/4" (10.80 cm x 10.80 cm)	5/16"	12.50	100


TRIM

			NUMBER	PIECES/ CARTON	GROUP
	Wall Bullnose (6" side)	2 x 6	S-4269	100	1■, 2▲, 3, 4, 5
	Wall Bullnose Corner	2 x 2	SN-4269	250	1■, 2▲, 3, 4, 5
	Wall Bullnose	4-1/4 x 4-1/4	S-4449	100	1, 2, 3, 4, 5
	Wall Bullnose Corner	4-1/4 x 4-1/4	SCRL-4449	100	1, 2, 3, 4, 5
	Wall Bullnose	6 x 6	S-4669	50	1, 2, 4
	Wall Bullnose Corner	6 x 6	SCRL-4669	50	1, 2, 4
	Radius Bullnose	4-1/4 x 4-1/4	A-4402	84	1■, 4
	Radius Bullnose Corner	4-1/4 x 4-1/4	ACRL-4402	30	1■, 4
	Radius Bullnose	6 x 6	A-3602	44	1■
	Radius Bullnose Corner	6 x 6	ACRL-3602	20	1■
	Radius Bullnose (6" side)	2 x 6	A-4200	100	1■, 2▲, 3, 4, 5
	Radius Bullnose Outcorner	2 x 2	AN-4200	200	1■, 2▲, 3, 4, 5
	Cove Base	4-1/4 x 4-1/4	A-3401	84	1, 2, 4
	Cove Base Corner Left or Right	4-1/4 x 4-1/4	ACR/L-3401	30	1■, 4
	Cove Base Corner Left or Right	4-1/4 x 4-1/4	SCR/L-3401	30	1, 2, 4
	Cove Base	6 x 6	A-3601	44	1■, 2▲, 4
	Cove Base Corner Left or Right	6 x 6	SCR/L-3601	20	1■, 2▲, 4
	Sanitary Cove Base (6" side)	4-1/4 x 6	S-3419T	60	1■, 2▲, 4
	Sanitary Cove Base Corner Left or Right	4-1/4 x 6	SCR/L-3419T	20	1■, 2▲, 4
	Sanitary Cove Base	6 x 6	S-3619T	40	1■, 4
	Sanitary Cove Base Corner Left or Right	6 x 6	SCR/L-3619T	20	1■, 2▲, 4
	V-Cap	2 x 6	WA-8262	66	1■, 2★
	V-Cap Outcorner	2 x 2	WAC-8262	40	1■, 2★
	V-Cap In-Corner	2 x 2	WAM-8262	200	1■
	Quarter Round	3/4 x 6	A-106	152	1■, 2▲, 4
	Quarter Round Outcorner	3/4 x 6	AC-106	120	1■, 2▲, 4
	Quarter Round Corner	3/4 x 3/4	AU-106	200	1■

- ◆ These items are special order (excluding colors 0025, 0090, & 0091), extended lead time may be required.
- ◇ These colors are special order and requires 1-2 weeks lead time.
- Not available in 0009, 0044, 0050, 0062, 0065, 0067, 0078, 0081, & 0095.
- ▲ Not available in 0037, 0038, 0039, 0040, 0041, 0064, & 0071.
- ✱ Not available in 0045.
- ★ Only available in 0049.

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:
Wall: 1/16"
RELATIVE PRICING: Low to Medium

SHADE VARIATION

LOW (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	WALL RESULT
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbs.
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

USAGE

FLOORS	WALLS	COUNTERTOPS
	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

*Matte finish only. Darker colors may show scratches.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

AMERICAN OLEAN®
PROVEN IN TILE™

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

