



BRIGHT & MATTE PROFILES™

GLAZED CERAMIC WALL

WALL



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

BRIGHT & MATTE PROFILES™

A rich color palette creates a look that is classically beautiful and infused with exquisite luxury. Multiple finishes offer versatility for increased visual appeal. Experience subway tile with traditional or contemporary elements from Bright & Matte Profiles.




Cover and above photos feature Bright & Matte Profiles Ice White 3 x 6 Bevel and Bright & Matte Linea™ Bright White 2 x 6 chair rail on the wall.

BRIGHT & MATTE PROFILES™

GLAZED CERAMIC WALL


BRIGHT




ICE WHITE 0025 (2)




BISCUIT 0091 (2)




SAND DOLLAR 0050 (3) ❖




CAPPUCCINO 0078 (2) ❖



NUTMEG 0037 (3) ❖




LIGHT SMOKE 0042 (2)




GLOSS BLACK 0049 (3)


MATTE




DESIGNER WHITE 0061 (1)




MATTE BISCUIT 0092 (1)




MATTE SAND DOLLAR 0067 (3) ❖



MATTE CAPPUCCINO 0009 (2) ❖



MATTE NUTMEG 0039 (3) ❖



MATTE BLACK 0064 (3)

BEVEL



MATTE DESIGNER WHITE 0061 (1)



ICE WHITE 0025 (2)



BISCUIT 0091 (2)



MATTE BISCUIT 0092 (1)





LIGHT SMOKE 0042 (2)

(1), (2) & (3) notations indicate price group, (1) being the least expensive.
❖ These items are made to order and require 6-8 weeks for delivery from date of order.






BRIGHT & MATTE PROFILES™

GLAZED CERAMIC WALL

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	3 x 6 Wall Tile	3" x 6" (7.50 cm x 15.20 cm)	5/16"	12.50	100
	3 x 6 Bevel Wall Tile ♦	3" x 6" (7.50 cm x 15.20 cm)	3/8"	10.40	80

TRIM

			NUMBER	PIECES/ CARTON
	Wall Bullnose (6" side)	3 x 6	S-4369	100
	Wall Bullnose (3" side)	3 x 6	S-4639	100
	Wall Bullnose Corner	3 x 6	SCR/L-4369	100
	Cove Base (6" side) †	3 x 6	A-3361	36
	Cove Base Corner †	3 x 6	SCR/L-3361	36

♦ Bevel only available in Ice White 0025, Light Smoke 0042, Matte Designer White 0061, Biscuit 0091 and Matte Biscuit 0092.

† Only available in Ice White 0025 and Biscuit 0091

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:
Wall: 1/16"

RELATIVE PRICING: Medium

SHADE VARIATION



LOW
(V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	WALL RESULT
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbs.
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

FLOORS	WALLS	COUNTERTOPS
	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Matte finish only. Darker colors may show scratches.

▲ Bevel wall tile and gloss finish not suitable for this application.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.



POST-CONSUMER
RECYCLED MATERIALS



PRE-CONSUMER
RECYCLED MATERIALS



MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2017 AMERICAN OLEAN (12/17)



AMERICAN OLEAN®
PROVEN IN TILE™