

ENTOURAGE™
REFLUENCE™
GLASS



Photo features Refluence Waterfall Random Linear mosaic on the wall.



RANDOM LINEAR GLASS MOSAIC



WHITE CAP RE08



WATERFALL RE09



STREAM RE10



CAVERN RE11



GROTTO RE12



TORRENT RE13

SIZES

| | THICKNESS | SQ. FT./ CARTON | PIECES/ CARTON |
|---|-----------|-----------------|----------------|
| <p>Random Linear Glass Mosaic ■ 13-1/8" x 12" Sheet (33.34 cm x 30.48 cm Sheet)</p> | 5/16" | 10.00 | 10 |

■ Mesh-mounted

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:
Mosaic: 1/8"

RELATIVE PRICING: High

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

| | ASTM# | MOSAIC RESULT |
|---------------------|-------|---------------|
| Water Absorption | C373 | < 0.5% |
| Breaking Strength | C648 | > 100 lbs. |
| Scratch Hardness | MOHS | 4.0 |
| Chemical Resistance | C650 | Resistant |
| Abrasion Resistance | C1027 | N/A |

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

| FLOORS | WALLS | COUNTERTOPS |
|--------|-------|-------------|
| | | |

APPLICATIONS

| | TARGET DCOF WET | SUITABLE |
|--|-----------------|----------|
| Dry & Level – Interior Floor | N/A | |
| Wet & Level – Interior Floor | ≥ 0.42 | |
| Shower Floors (Residential or Light Commercial) | ≥ 0.42 | |
| Exterior Floor Applications (including pool decking & other wet areas with minimal footwear) | ≥ 0.60 | |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A | |
| Countertops | N/A | |
| Pool Linings | N/A | |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

NOTES

For additional information refer to “Factors to Consider” at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.