


.

## AMERICAN OLEAN®







# PLAYSCAPES™

Inspired by mid-century modernism, Playscapes<sup>™</sup> showcases a lively array of unique wall tile shapes. Each piece has a translucent glaze with an undulated surface mimicking a handcrafted structure. Seven tasteful hues, designed to express today's color trends, are included in this collection for vibrant or delicate spaces. Three different shapes – a 6" Arabesque, 4" Hexagon, and a 3 x 6 Harlequin embody their own sense of style, perfect for building your personal design aesthetic.

Cover features Peony 3 x 6 Harlequin wall tile. Above photo features Sky, Meringue, Pitch black, Linen & Silverside 4" Hexagon.

## **PLAYSCAPES<sup>™</sup>** AMERICAN OLEAN® GLAZED CERAMIC WALL

#### FINISHES: GLOSSY

#### USAGE MATERIAL PRICING SPECIAL FEATURES LOW τÆ FLOOP EXTERIOR FLOOR SHOWER FLOOR

SEE CHARTS FOR FULL PRODUCT DETAILS.

#### **6" ARABESQUE WALL TILE**













WALL


MIDNIGHT BLUE PS76

**4" HEXAGON WALL TILE** 



SILVERSIDE PS73 PITCH BLACK PS71

PEONY PS75





3x6 HARLEQUIN WALL TILE



**MERINGUE PS70** 







SILVERSIDE PS73 PITCH BLACK PS71



PEONY PS75



SKY PS74





VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# PLAYSCAPES™

GLAZED CERAMIC WALL

## AMERICAN OLEAN®

#### FINISHES: GLOSSY



SEE CHARTS FOR FULL PRODUCT DETAILS.

#### SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
$\Diamond$	6" Arabesque Wall Tile	5-1/4" x 6" (13.33 cm x 15.24 cm)	5/16"	10.80	90
$\bigcirc$	4" Hexagon Wall Tile	4-1/4" x 4-7/8" (10.88 cm x 12.57 cm)	5/16"	3.00	30
$\Diamond$	3 x 6 Harlequin Wall Tile	3" x 6" (7.61 cm x 15.31 cm)	5/16"	5.04	84

#### APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	•
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of  $\geq$  0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest<sup>™</sup>, visit americanolean.com/DCOF.

#### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

#### FEATURES



PRE-CONSUMER RECYCLED MATERIALS



888.AOT.TILE

AMERICANOLEAN.COM



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

|--|

# Jolly 1/2 x 12 S1/212J 6 Cards\*

WALL

\* 4 Pieces per card

#### INSTALLATION

Grout Joint Recommendation	Shade Variation
Wall: 1/6"	
	LOW (\/1)

#### PERFORMANCE CHARACTERISTICS

	ASTM#	WALL RESULT
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbs.
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

#### NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.



©2021 AMERICAN OLEAN (09/21)

AMERICAN OLEAN®

PROVEN IN TILE"

