

ULTRA MODERN™  
COLORBODY™ PORCELAIN




Photo features Ultra Modern Beyond Beige 24 x 24 Unpolished on the floor.

# ULTRA MODERN™ COLORBODY™ PORCELAIN FLOOR

Offering a contemporary visual in an appealing commercial color palette, Ultra Modern™ has become a go-to product for large-scale projects requiring a combination of form, function, and cost efficiency. This double-load porcelain tile offers a visual consistency that most minimalist design schemes demand. TruEdge™ rectification means tighter grout joints while two finish treatments—polished and unpolished—offer design versatility. Six hues ranging from Infinite Cream to Futuristic Black comprise the sophisticated color palette.

ULTRA MODERN™

## COLORBODY™ PORCELAIN FLOOR TILE - UNPOLISHED



INFINITE CREAM UM05 (1)



BEYOND BEIGE UM06 (1)




PROGRESSIVE GRAY UM07 (1)



VISIONARY BROWN UM08 (1)



ADVANCED CHARCOAL UM09 (1)



FUTURISTIC BLACK UM10 (2)

## COLORBODY™ PORCELAIN FLOOR TILE - POLISHED



INFINITE CREAM UM05 (1)



BEYOND BEIGE UM06 (1)



PROGRESSIVE GRAY UM07 (1)



VISIONARY BROWN UM08 (1)



ADVANCED CHARCOAL UM09 (1)



FUTURISTIC BLACK UM10 (2)

(1) & (2) notations indicate price group, (1) being the least expensive.





All or select items within this series meet the requirements for these qualifications. For more information visit [americanolean.com](http://americanolean.com).

AMERICANOLEAN.COM



Photo features Ultra Modern™ Beyond Beige 24 x 24 Unpolished on the floor.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	24 x 24 Floor Tile *	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	3/8"	15.20	4
	12 x 24 Floor Tile *	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	3/8"	15.12	8

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	S-43C9	30
	Cove Base	6 x 12	S-36C9T	20
	Cove Base Outcorner	6 x 1	SC-36C9T	10

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.  
\* Modular sizes

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)

RELATIVE PRICING: Medium

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.  
\* Unpolished finish only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.