

2.5 mm | 20 Mil  
**BELLANT™**  
FLEXIBLE GLUE DOWN

**PROSERIES™**  
LUXURY VINYL FLOORING  
daltile®

36 x 36 CONCRETE LOOK TILES



NATURAL BEIGE BL30



CONCRETE GREY BL32

18 x 18 FABRIC / ENCAUSTIC LOOK TILES



WOVEN WHITE BL34



WOVEN GREY BL35



CAFÉ BL36

2.5 mm | 20 Mil  
**BELLANT™**  
FLEXIBLE GLUE DOWN



## DESIGN & SIZE

Product Type:	LVT Dry Back
Thickness:	2.5 mm
Wear Layer:	20 Mil (0.508 mm)
Finish:	SuperGuard™ Technology
Size:	36" W x 36" L (Concrete) 18" W x 18" L (Fabric & Encaustic)
Sq. Ft./Carton:	54/36
Pieces/Carton:	6/16
Weight:	7.5 lbs per piece   46.1 lbs per carton (Concrete) 1.9 lbs per piece   31.1 lbs per carton (Fabric & Encaustic)
Installation & Adhesive:	Glue down and install using ProSeries by Daltile Adhesive; see <a href="http://daltile.com/LVF">daltile.com/LVF</a> for more recommended installation and adhesive information
* Special Order Transitions:	Slim Trim 4-in-1 Transition, Extra Tall Stair Nose, Full Round Stair Tread, Round Stair Nose, Quarter Round, and Slim Cap.

## SERVICE

Warranty:	Limited Lifetime Residential Warranty Limited 15 Year Multifamily Warranty Limited 15 Year Light Commercial Warranty Limited 15 Year Commercial Warranty
-----------	---

## PERFORMANCE

Construction:	Commercial Grade Luxury Vinyl Flooring; 100% Virgin Vinyl
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - $\pm 0.016$ in. per lin ft.
Thickness:	ASTM F386 - Passes - Nominal $\pm 0.005$ in
Flexibility:	A ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - $\leq 0.024$ in. per lin ft.
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Slip Resistant:	ASTM D2047 - Passes - $> 0.6$ Wet, 0.6 Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1515 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Passes - $\geq 0.45$ watts/cm <sup>2</sup> , Class 1
Smoke Density:	ASTM E662 - Passes



7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of  
Daltile® products and information,  
visit our website at [daltile.com/LVF](http://daltile.com/LVF)



©2024 Dal-Tile Corporation (04/24)