2.0 mm | 12 mil CYROSE™ GLUE DOWN

# PROSERIES LUXURY VINYL FLOORING Nadaltile





SIZES:	
	6 x 48
	0 X 48


# 6 x 48 WOOD LOOK PLANKS



WHITE ASH CY30



COASTAL GREY CY31



BARNWOOD CY34



HONEY MAPLE CY32



EARLY AMERICAN CY33











REDUCING EAS

100% WATERPROOF

### **DESIGN & SIZE**

Product Type: Glue Down LVF
Installation: Glue Down
Thickness: 2.0 mm

Wear Layer: 12 mil (0.3048 mm) Finish: SuperGuardX™ Technology

Size: 6" W x 48" L Plank

Underlayment: N/A
Bevel: No Bevel
Embossing: Embossed

Plank Variation: 6
Sq. Ft./Carton: 54
Pieces/Carton: 27

Weight: 1.35 lbs per piece | 37.7 lbs per carton
Installation Glue down and install using ProSeries by Adhesive: Daltile Adhesive; see daltile.com/LVF for more recommended installation

and adhesive information

## **SERVICE**

Warranty: Limited 25 Year Residential Warranty

Limited 10 Year Multifamily Unit Warranty Limited 7 Year Light Commercial Warranty

### PERFORMANCE & CHARACTERISTICS

Construction: Light Commercial Grade Luxury Vinyl

Flooring; 100% Virgin

Classification: ASTM F1700 - Class III, Type A - Smooth,

Type B - Embossed

Squareness: ASTM F2421 - Passes - ±0.010" max Size and Tolerance: ASTM F2421 - Passes - ±0.016 in. /

linear foot

Thickness: ASTM F386 - Passes - as specified ±0.005 in

Flexibility: ASTM F137 - Passes - 1" mandrel

Dimensional Stability: ASTM F2199 - Passes - 0.020 in. / linear

foot max

Static Load Limit: ASTM F970 - Passes, modified at 1000 psi

Coefficient of Friction (Slip Resistance) Residual Indentation:

efficient of Friction ASTM D2047 - Passes - ≥0.80 (Dry)

ASTM F1914 - Passes - Average less than 8% maximum single reading 10%

Resistance To Chemicals: ASTM F925 - Passes - No more than a

slight change

Resistance To Light: ASTM F1515 - Passes -  $\Delta E \le 8$ Resistance To Heat: ASTM F1514 - Passes -  $\Delta E \le 8$ 

Critical Radiant Flux: ASTM E648 - Passes - Class 1 (> 0.45 W/cm²)

Smoke Density: ASTM E662 Part A - Passes - < 450







