

2.5 mm | 20 Mil
ELIXEN™
GLUE DOWN

PROSERIES™
LUXURY VINYL FLOORING
daltile®

7 X 47 WOOD LOOK PLANKS



SONOMA OAK EX30



WHITE OAK EX31



VINTAGE PINE EX32



ASHWOOD EX33



DRIFTWOOD EX34



EXOTIC TEAK EX35



BALCK WALNUT EX36



RUSTIC JAVA EX37



ROSEWOOD EX38

2.5 mm | 20 Mil
ELIXEN™
 GLUE DOWN



DESIGN & SIZE

Product Type:	Glue Down LVF
Thickness:	2.5 mm
Wear Layer:	20 Mil (0.508 mm)
Finish:	SuperGuard™ Technology
Size (nominal):	7" W x 47" L Plank
Size (actual):	180 mm x 1,200 mm
Packaging:	34.88 sq. ft. per carton 15 pieces per carton
Weight:	1.94 lbs per piece 30.2 lbs per carton
Installation & Adhesive:	Glue down and install using ProSeries by Daltile Adhesive; see daltile.com/LVF for more recommended installation and adhesive information

SERVICE

Warranties:	Limited 10 Year Light Commercial Limited 15 Year Residential
-------------	---

PERFORMANCE & CHARACTERISTICS

Construction:	Commercial Grade Luxury Vinyl Flooring; 100% Virgin
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2421 - Passes - $\pm 0.010"$ max
Size and Tolerance:	ASTM F2421 - Passes - ± 0.016 in. / linear foot
Thickness:	ASTM F386 - Passes - as specified ± 0.005 in
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in. / linear foot max
Static Load Limit:	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Resistance To Chemicals:	ASTM F925 - Passes - No more than a slight change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Class 1 (> 0.45 W/cm ²)
Smoke Density:	ASTM E662 Part A - Passes - < 450
Smoke Density:	ASTM E662 - Passes



7834 C.F. Hawn Freeway,
 Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com/LVF



©2020 Dal-Tile Corporation (07/20)