

CONCRETE  
LOOK


USAGE



LOW HIGH

SEE CHARTS FOR FULL  
PRODUCT DETAILS

SIZES:



FINISHES: MATTE

\*Linear Options™

COLOR PALETTE



WHITE  
IMAGE



BEIGE  
HAZE



GREEN  
MIST



GRAY  
FOG



BROWN  
VISION



BLACK  
SHADOW

COLORBODY™ PORCELAIN FLOOR TILE with STEPWISE™



WHITE IMAGE PN94



BEIGE HAZE PN95



GREEN MIST PN97



GRAY FOG PN98



BROWN VISION PN96



BLACK SHADOW PN99



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™





SIMPLICLEAN™

# PLAZA NOVA™




COLORBODY™ PORCELAIN

CONCRETE LOOK

## SIZES

|  |                       |  | Thickness | Sq. Ft./<br>Carton | Pieces/<br>Carton |
|--|-----------------------|--|-----------|--------------------|-------------------|
|  | 12 x 24<br>Field Tile | (11-13/16" x 23-5/8")<br>(30.00 cm x 60.00 cm)   | 3/8"      | 9.68               | 5                 |
|  | 12 x 12<br>Field Tile | (11-13/16" x 11-13/16")<br>(30.00 cm x 30.00 cm) | 3/8"      | 10.65              | 11                |

## LINEAR OPTION™ SIZES

|  |                      |   | Thickness | Sq. Ft./<br>Carton | Pieces/<br>Carton |
|--|----------------------|---|-----------|--------------------|-------------------|
|  | 6 x 24<br>Field Tile | (6" x 23-5/8")<br>(14.63 cm x 60.00 cm) | 3/8"      | 10.65              | 11                |
|  | 4 x 24<br>Field Tile | (4" x 23-5/8")<br>(9.73 cm x 60.00 cm)  | 3/8"      | 6.46               | 10                |
|  | 2 x 24<br>Field Tile | (2" x 23-5/8")<br>(4.67 cm x 60.00 cm)  | 3/8"      | 6.66               | 20                |

Additional linear and rectangular sizes are also available..

## APPLICATIONS

|  | Target<br>DCOF wet | Suitable |
|--|--------------------|----------|
| Dry & Level – Interior Floor   | N/A                | ✓        |
| Wet & Level – Interior Floor   | ≥ 0.42             | ✓        |
| Shower Floors (Residential or Light Commercial)  | ≥ 0.42             | ✓*       |
| Exterior Floor Applications<br>(including patios, pool decking & other<br>wet areas with minimal footwear) | ≥ 0.60             |          |
| Ramps & Inclines   | ≥ 0.65             |          |
| Walls/Backsplashes   | N/A                | ✓        |
| Countertops  | N/A                | ✓        |
| Pool Linings   | N/A                |          |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

## APPLICATION NOTES:




Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

## PERFORMANCE CHARACTERISTICS

|                     | ASTM# | Result    |
|---------------------|-------|-----------|
| Water Absorption    | C373  | < 0.5%    |
| Breaking Strength   | C648  | > 275 lbs |
| Scratch Hardness    | MOHS  | 8.0       |
| Chemical Resistance | C650  | Resistant |

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).


## TRIM

|   | Type                    | Number   | Size   | Pieces/<br>Carton |
|---|-------------------------|----------|--------|-------------------|
|  | Bullnose                | S-43C9   | 3 x 12 | 30                |
|  | Cove Base*              | P-36C9T  | 6 x 12 | 22                |
|  | Cove Base*<br>Outcorner | PC-36C9T | 1 x 6  | 15                |

\* Cove base and cove base outcorner are clay body ceramic and are suitable for applications in non-freezing climates only.

Bullnose, cove base, and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

## INSTALLATION

| Grout Joint Recommendation   | Shade Variation   |
|--|---|
| 1/8" (3/16" when multiple sizes are installed in a modular pattern and/or when tile with a length 15" or greater is installed in a staggered brick-joint pattern. Overlap should not exceed 33%) |  Medium (V2) |

## DURABILITY

### Floor Surface Wear Resistance

|   |                       |   |                                    |
|---|-----------------------|---|------------------------------------|
| 1 | Residential Bathrooms | 3 | All Residential / Light Commercial |
| 2 | All Residential Areas | ④ | All Residential / Commercial       |

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).