

MYSTONE LIMESTONE™

COLORBODY™ PORCELAIN

STARE

TILE SO STUNNING YOU CAN'T TAKE YOUR EYES OFF IT

STONE LOOK

USAGE

-  FLOOR
-  WALL
-  COUNTERTOP
-  SHOWER FLOOR
-  EXTERIOR FLOOR
-  STEPWISE™
-  TRU-EDGE™
-  MADE IN THE U.S.A.
-  LARGE FORMAT
-  MOSAIC/DECO
-  ENCAUSTIC
-  TERRAZZO
-  PAVER
-  CUSTOMIZE
-  FLEXFIT™

SPECIAL FEATURES

SIZES:



FINISHES: STRUCTURED | MATTE | SATIN

COLORBODY™ PORCELAIN – SHOWN AS 12 x 24



IVORY M7EK



SAND M7EJ



TAUPE M7EH

14 x 15 FOGLIE MOSAIC



IVORY M8LR



SAND M8LS



TAUPE M8LY

12 x 11.5 MOSAIC BLEND



MIX TAUPE M8LP

	MATTE					SATIN			STRUCTURED			2CM PAVER		FOGLIE MOSAIC	BULLNOSE
	12 x 24	24 x 24	30 x 30	30 x 60	48 x 48	30 x 30	30 x 60	12 x 24	30 x 30	48 x 48	32 x 32	24 x 48	14 x 15	3 x 30	
IVORY	M7EK	M7EF	M7E7	M7E3	M907	M7F3	M7EX	M7ET	M7EP	M90C	M7FK	M7SS	M8LR	M8HX	
SAND	M7EJ	M7EE	M7E6	M7E2	M908	M7F2	M7EW	M7ES	M7EN	M70D	M7FJ	M7SR	M8LS	M8JO	
TAUPE	M7EH	M7E9	M7E5	M7E1	M909	M7EZ	M7EV	M7ER	M7EM	M90E	M7FH	M7SQ	M8LY	M8HX	



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT*
*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.









NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

MYSTONE LIMESTONE™

COLORBODY™ PORCELAIN

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	30 x 60 Floor Tile (Matte & Satin)	(29-1/2" x 59-3/64") (750 mm x 1500 mm)	3/8"	24.22	2
	48 x 48 Floor Tile (Matte & Structured)	(47-1/4" x 47-1/4") (1200 mm x 1200 mm)	3/8"	15.50	1
	24 x 48 Paver	(23-5/8" x 47-1/4") (600 mm x 1200 mm)	3/4"	7.75	1
	32 x 32 Paver	(31-1/4" x 31-1/4") (795 mm x 795 mm)	3/4"	6.89	1
	30 x 30 Floor Tile (Matte, Satin & Structured)	(29-1/2" x 29-1/2") (750 mm x 750 mm)	3/8"	12.16	2
	24 x 24 Floor Tile	(23-17/40" x 23-17/40") (595 mm x 595 mm)	3/8"	11.63	3
	12 x 24 Floor Tile (Matte & Structured)	(11-13/16" x 23-9/16") (300 mm x 600 mm)	3/8"	11.63	6
	14 x 15 Foglie Mosaic	(14-15/16" x 13-7/16" Sheet) (380 mm x 342 mm Sheet)	3/8"	4.52	4
	12 x 11.5 Mosaic Blend	(11-13/16" x 12-1/125" Sheet) (300 mm x 305 mm Sheet)	3/8"	3.89	4

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓**
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	


A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:


Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Not applicable for Satin finish
** 2CM Pavers only

TRIM

Type	Size	Pieces/ Carton
 Bullnose	3 x 30	14

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%).	 Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0 - 8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex TRIM modified thin-set is recommended for installation.

REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.