

**WOOD  
LOOK**

**USAGE**



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

**SIZES:**



**FINISHES: MATTE**

**COLORBODY™ PORCELAIN – SHOWN AS 8 x 48**



WHITE M9E8



NATURAL M9EA



SAND M9E9



CARAMEL M9EC

	MATTE			BULLNOSE	
	8 x 48	12 x 48	9 x 71	2.5 x 24	3 x 36
WHITE	M9E8	M9F8	M9DL	M9JS	M9JM
NATURAL	M9EA	M9FA	M9DM	M9JU	M9JP
SAND	M9E9	M9F9	M9DN	M9JT	M9JN
CARAMEL	M9EC	M9FC	M9DP	M9JV	M9JQ



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT\*  
\*Not Applicable to Mesh-Mounted Mosaics




CLIMATEPRO™



SIMPLICLEAN™

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	9 x 71 Floor Tile	(8-7/8" x 70-7/8") (225 mm x 1800 mm)	3/8"	17.44	4
	12 x 48 Floor Tile	(11-5/8" x 47-1/32") (296.5 mm x 1194.9 mm)	3/8"	11.63	3
	8 x 48 Floor Tile	(7-7/8" x 47-1/4") (200 mm x 1200 mm)	3/8"	10.33	4

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltille.com/DCOF](http://daltille.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

TRIM

	Type	Size	Pieces/ Carton
	Bullnose	2.5 x 24	15
	Bullnose	3 x 36	13

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltille.com/information/TestResults](http://daltille.com/information/TestResults).

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [daltille.com/Factors](http://daltille.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltille.com/LargeTiles](http://daltille.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex TRIM modified thin-set is recommended for installation.

 REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltille.com](http://daltille.com).