


WALL

USAGE



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:



FINISHES: GLOSSY

CERAMIC WALL TILE – 3 x 12 RIPPLE



BRIGHT WHITE US10



BRIGHT CARMEL US11



BRIGHT SMOKE US12



BRIGHT GREY US13



BRIGHT STORM US14




BRIGHT GREEN US15



BRIGHT SCARLET US16

CERAMIC WALL TILE – 3 x 12 WAVE




BRIGHT WHITE US10



BRIGHT CARMEL US11



BRIGHT SMOKE US12



BRIGHT GREY US13



BRIGHT STORM US14



BRIGHT GREEN US15



BRIGHT SCARLET US16



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT
*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	3 x 12 Ripple	(3" x 12") (7.50 cm x 30.00 cm)	1/4"	6.03	25
	3 x 12 Wave	(3" x 12") (7.50 cm x 30.00 cm)	5/8"	3.44	14

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltilo.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	> 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltilo.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltilo.com/Factors.

