

SIZES:



16 x 48
Deco
Wall Tile



15 x 48
Wall Tile



15 x 48
Diamond
Wall Tile



15 x 48
Deco
Wall Tile



15 x 15
Triangle
Mosaic

FINISHES: MATTE

DECORATIVE

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



CERAMIC

LOW HIGH

CERAMIC WALL TILE – FLAT



ROSE M19J



PURPLE M19K



TAUPE M19L



CREAM M19N



ANTHRACITE M19Q



SAGE M19R



BLUE M19S



WHITE M19J

CERAMIC WALL TILE – PATTERNS



ROSE M1A7




PURPLE M1A8



TAUPE M1J6



CREAM M1A9



ANTHRACITE M1J7



SAGE M1AD



BLUE M1J8



WHITE M1AA

CERAMIC WALL TILE – 15 x 48 DECOS



CARIOCA CREAM M1AN



CARIOCA WHITE M1AP



ETOILE PURPLE M2U3



ETOILE BLUE M2U4

CERAMIC WALL TILE – 48 x 48 DECOS

Delivered in three 16 x 48 pieces




PEONY CREME M2U7



PEONY WHITE M2U8

CERAMIC MOSAICS



WHITE M3JA



CREAM M3J8




TAUPE M3J6




ANTHRACITE M3JD




ROSE M3J2



PURPLE M3J4



SAGE M3JF



BLUE M3JH



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT
*Not Applicable to Mesh-Mounted Mosaics



SIMPLICLEAN™

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	16 x 48 Deco Wall Tile	(15-3/4" x 47-1/4") (400 mm x 1200 mm)	15/64"	15.50	3
	15 x 48 Wall Tile	(15-3/4" x 47-1/4") (400 mm x 1200 mm)	15/64"	31.00	6
	15 x 48 Diamond Wall Tile	(15-3/4" x 47-1/4") (400 mm x 1200 mm)	5/16"	25.83	5
	15 x 48 Deco Wall Tile	(15-3/4" x 47-1/4") (400 mm x 1200 mm)	5/16"	31.00 (Carioca)	6 (Carioca)
				20.67 (Etoile)	4 (Etoile)
	15 x 15 Triangle Mosaic	(15-3/4" x 15-3/4" Sheet) (400 mm x 400 mm Sheet)	15/64"	6.89	4

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Random (V4) Mosaic & Decos  Low (V1) Flat & Patterns

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	> 120 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

 PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.