

TERRAZZO LOOK

USAGE

-  FLOOR
-  WALL
-  COUNTERTOP
-  SHOWER FLOOR
-  EXTERIOR FLOOR
-  STEPWISE™
-  TRU-EDGE™
-  MADE IN THE U.S.A.
-  LARGE FORMAT
-  MOSAIC/DECO
-  ENCAUSTIC
-  TERRAZZO
-  PAVER
-  CUSTOMIZE
-  FLEXFIT™

SPECIAL FEATURES

SIZES:



48 x 48
Floor Tile



24 x 48
Floor Tile



24 x 24
Floor Tile



2 x 2
Mosaic

FINISHES: MATTE

COLORBODY™ PORCELAIN – SHOWN AS 24 x 24




WHITE M8E6




BEIGE M8E7



LIGHT GREY M8E8



DARK GREY M8E9



BLACK M8EA

2 x 2 MOSAIC



WHITE MOKX



BEIGE MOKY



LIGHT GREY MOKZ

MATTE

24 x 24


24 x 48

48 x 48

BULLNOSE

3 x 24

WHITE	M8E6	M8DR	M8D9	MR5X
BEIGE	M8E7	M8DS	M8DA	MR5Y
LIGHT GREY	M8E8	M8DT	M8DC	MR5Z
DARK GREY	M8E9	M6DU	M8DD	MR60
BLACK	M8EA	M6DV	M8DE	MR61



LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT™
*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™



SIMPLICLEAN™

TERRAZZO LOOK

PINCH™
COLORBODY™ PORCELAIN

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	48 x 48 Floor Tile	(47-3/16" x 47-3/16") (1200 mm x 1200 mm)	3/8"	15.50	1
	24 x 48 Floor Tile	(23-17/40" x 47-1/20") (595 mm x 1195.07 mm)	3/8"	15.50	2
	24 x 24 Floor Tile	(23-3/8" x 23-3/8") (595 mm x 595 mm)	3/8"	11.63	3
	2 x 2 Mosaic (Mesh-mounted)	(11-13/16" x 11-13/16" Sheet) (300 mm x 300 mm Sheet)	3/8"	3.88	4

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* 2 x 2 mosaic tile only

TRIM

Type	Size	Pieces/ Carton
 Bullnose	3 x 24	14

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 High (V3) Floor  Random (V4) Mosaic

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex TRIM modified thin-set is recommended for installation.

