


## SURETREAD SURFACE




Red OQ81 (1)




Wheat OQ79 (2)




Golden Brown OQ75 (2)



Bronze Clay OQ86 (2)




Gray OQ76 (2)



Storm Gray OQ82 (2)



Chocolate OQ88 (2)



Black OQ73 (2)

## PAVER SURFACE



Red OQ84 (1)



Wheat OQ80 (2)



Golden Brown OQ78 (2)




Bronze Clay OQ87 (2)



Gray OQ85 (2)



Storm Gray OQ83 (2)



Chocolate OQ89 (2)



Black OQ74 (2)

(1) and (2) indicate price groups, (1) being the least expensive.

## Protect The Pep In Your Step

- **NATURAL RESISTANCE**
  - Available in a smooth paver surface and a textured tread surface
  - Durable, natural product with low moisture absorption
  - Textured surface provides excellent slip-resistance
  
- **COMMERCIAL APPEAL**
  - Withstands extreme amounts of weight such as kitchen equipment and auto displays
  - Tread surface prevents grease and water from building under feet
  - Quarry Guard makes it easier to clean and stain-resistant



**PRE-CONSUMER  
RECYCLED MATERIALS**



**MADE IN THE U.S.A.**


All or select items within this series meet the requirements for these qualifications. For more product information, visit [daltile.com](http://daltile.com).

### USAGE

Floors      Walls      Countertops

**F      W      C**

## SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	6 x 6 Floor Tile	(6" x 6") (15.20 cm x 15.20 cm)	3/8"	12.00	48

Sizing differences may exist between gray and red colors. When mixing colors, check actual samples to ensure sizing compatibility.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓
Ramps & Inclines	≥ 0.60	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.






Suitable for industrial installations requiring high compressive strength.

Subject to Oils: Absorbs oils, grease and other liquids to keep floors slip-resistant, yet does not contaminate the surface. Proper cleaning methods easily remove any contaminants that do get absorbed into the tile.

# QUARRY GUARD™

QUARRY GUARD™ IMPROVES THE GROUT RELEASE AND STAIN RESISTANCE OF THE TILE, RESULTING IN EASIER CLEAN-UP WITH INSTALLATION AND TILE THAT IS LESS LIKELY TO GET STAINED IN THE FUTURE.


## TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	P-1665	6 x 6	48
 Bullnose Corner	PC-1665	6 x 6	26
 Cove Base	P-3665	6 x 6	48
 Cove Base Corner	PCR-L-3665	6 x 6	26
 Cove Base Inside Corner	PB-3665	3/4 x 6	50

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Suretread trim is a smooth trim. Tread surface is not available on trim.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/8"	 Medium (V2)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 3.0%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special care should be taken when grouting; a grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

It is necessary to follow the proper procedures and recommendations from the grout and maintenance products' manufacturers.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).

7834 C. F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



© 2018 Daltile (8/18)