



WOOD LOOK

ACACIA VALLEY™
COLORBODY™ PORCELAIN



 daltile®
IMAGINE WHAT'S POSSIBLE™

ACACIA VALLEY™

COLORBODY™ PORCELAIN

The Look of Exotic Hardwood with the Performance of Tile

Rich in detail and color, Acacia Valley™ is designed to replicate the exotic visual of Acacia wood, which is often associated with high-end furniture. Because it was created with Tru-Edge™ technology, Acacia Valley can be installed with minimal grout joints, further enhancing the natural hardwood look. It also is designed with durability and performance in mind allowing it to be used in any room, including bathrooms and kitchens. Acacia Valley gives any space the sophistication and style of expensive hardwood with the durability and versatile use of porcelain tile.

- VISUAL APPEAL

- Large plank sizes can be used together to create a typical hardwood visual.
- Tru-Edge™ allows for tighter grout joints and a more wood-like installation.

- WARM, UNIQUE COLOR PALETTE

- Available in natural and rich hues for enhanced design appeal.

- HIGH PERFORMANCE

- Porcelain tile is suitable in wet areas, such as bathrooms and kitchens.


WOOD LOOK

USAGE



SEE CHARTS FOR FULL
PRODUCT DETAILS

SPECIAL FEATURES



Cover photo features Ark 9 x 36 and 6 x 36 field tile in a random linear pattern on the floor.
Above photo features Ark 6 x 36 and 9 x 36 field tile in a random linear pattern on the step landing.

WOOD LOOK

ACACIA VALLEY™

COLORBODY™ PORCELAIN

SIZES:

9 x 36
Floor Tile

6 x 36
Floor Tile

FINISHES: MATTE

COLOR PALETTE



ASH



ARK



RIDGE

FLOOR TILE



ASH – 6 x 36 AV05, 9 x 36 AV13



ARK – 6 x 36 AV06, 9 x 36 AV14



RIDGE – 6 x 36 AV08, 9 x 36 AV16



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT





CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	9 x 36 Floor Tile (AV13, AV14, AV16)	(8-7/8" x 35-1/4") (22.50 cm x 89.50 cm)	3/8"	13.02	6
	6 x 36 Floor Tile (AV05, AV06, AV08)	(5-3/4" x 35-1/4") (14.70 cm x 89.50 cm)	3/8"	12.78	9

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.


APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
For additional information on test results, visit us at: daltille.com/information/TestResults .		

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to “Factors to Consider” at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltille® products and information,
visit our website at daltille.com.

