



WALL

ARTIGIANO™
GLAZED CERAMIC

ARTIGIANO™

GLAZED CERAMIC

Enjoy the Charm of Handcrafted Style

Inspired by the homes of southern Europe, Artigiano brings artisan appeal into any room. Its glossy, hand-painted appearance and irregular edges add to its rich, old-world look. Offered in seven earthy, neutral colors and two linear sizes, this resurgent design adds subtle charm to wall designs.

• ARTISAN APPEAL

- Captures the warmth and charm of old-world Europe
- Hand-painted look and irregular edges reflect the beauty and tradition of handmade tile
- Enjoy a handcrafted, artisan look

• CREATE SUBTLE FEATURE WALLS

- Offered in two linear sizes, ideal for creating backsplashes: 3" x 6" and 3" x 12"
- Neutral, earthy color palette easily coordinates with virtually any room design

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



CGLAZED CERAMIC



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

Cover and above photos feature Riviera Pompeii and Italian Alps 3 x 6 wall tile.

SIZES:



FINISHES: GLOSSY

WALL TILE



ITALIAN ALPS AR93



TREMITI SAND AR94



RIVIERA POMPEII AR95



VENICE STATUE AR96



MILAN ARENA AR97



ROMAN SKYLINE AR98



FLORENTINE GATES AR99



ITALIAN ALPS AR93



TREMITI SAND AR94



RIVIERA POMPEII AR95



VENICE STATUE AR96



MILAN ARENA AR97



ROMAN SKYLINE AR98



FLORENTINE GATES AR99



STAINPROOF



DENTPROOF



FIRE-RESISTANT



SIMPLICLEAN™

ARTIGIANO™

GLAZED CERAMIC

WALL

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	3 x 12 Wall Tile	(2-15/16" x 11-3/4") (7.50 cm x 30.00 cm)	5/16"	5.28	22
	3 x 6 Wall Tile	(2-15/16" x 5-7/8") (7.50 cm x 15.00 cm)	5/16"	5.28	44

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

LRV

Color #	LRV Illuminate-OBS: F02-02 (CWF)
AR93	85.3
AR94	43.0
AR95	38.6
AR96	19.4
AR97	10.3
AR98	34.9
AR99	4.5

TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose	S-4369 (6" Side)	3 x 6	44

INSTALLATION

Grout Joint Recommendation

1/8"

Shade Variation



PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

