



STONE LOOK

CONSULATE™

STONE ATTACHÉ™ COLLECTION – COLORBODY™ PORCELAIN

 daltile®
IMAGINE WHAT'S POSSIBLE™

CONSULATE™

STONE ATTACHÉ™ COLLECTION – COLORBODY™ PORCELAIN

Embody the Beauty and Strength of Stone with Consulate™

There's nothing quite like the sheer visual drama of stone, which is perfectly captured in both Consulate Antique and Consulate Quartzite. The Antique and Quartzite visuals will make any commercial or residential setting extraordinary. Consulate ColorBody™ porcelain tile displays a variety of naturally intense patterns.

- VISUAL STRENGTH
 - Antique visual conveys the smooth look of recovered, aged marble
 - Quartzite visual maximizes the intensity of quartzite's natural texture and richness
 - Both visuals offer unique and dramatic shade variations and veining to appeal to the most exquisite tastes
- SOPHISTICATED OPTIONS
 - Large format 12 x 24 and 24 x 48 sizes are offered
 - Textured surface suitable for exterior applications

STONE LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC

LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

Cover photo features Quartzite Embassy Silver textured 12 x 24 on the floor.
Above photo features Antique Concierge Sand 24 x 48 on the floor.

STONE LOOK

CONSULATE™

STONE ATTACHÉ™ COLLECTION – COLORBODY™ PORCELAIN

SIZES:



24 x 48
Floor Tile



12 x 24
Floor Tile

FINISHES: MATTE | TEXTURED

FLOOR TILE – ALL COLORS AVAILABLE IN UNPOLISHED & TEXTURED



CONCIERGE SAND ANTIQUE CS06



LIAISON BEIGE QUARTZITE CS08



PREMIER GREY ANTIQUE CS05



EMBASSY SILVER QUARTZITE CS07



SLIP RESISTANT



WATERPROOF



STAINPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™



VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

CONSULATE™

STONE ATTACHÉ™ COLLECTION – COLORBODY™ PORCELAIN

STONE LOOK

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48" Field Tile	(23-7/16" x 47") (59.50 cm x 119.30 cm)	3/8"	15.50	2
	12 x 24" Field Tile	(11-11/16" x 23-7/16") (29.65 cm x 59.50 cm)	3/8"	9.70	5

*Available in Matte finish only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:




Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Textured surface only

PRE-CONSUMER RECYCLED MATERIALS


All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose (Unpolished)	S-43F9	3 x 24	15
 Cove Base	S-36C9T	6 x 12	20
 Cove Base Corner	SC-36C9T	1 x 6	10

Bullnose, cove base and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%)	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance
1 Residential Bathrooms 3 All Residential / Light Commercial
2 All Residential Areas (4) All Residential / Commercial

NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at daltile.com/Factors.