



FLOOR | WALL

EMBOLD™
GLAZED PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature Embold™ Diamond Shimmer Silver and Dash Shimmer Silver 1-1/4 x 24 decorative accents on the floor and Portfolio™ Iron Grey 24 x 24 field tile on the floor.

Take Your Design to the Next Level with Embold™ Tile

When your head says “play it safe” and your heart says “bring the drama”, Embold tile gives you the confidence to have both. Featuring geometric patterns and metallic finishes, these linear 1 x 24 decorative accents are perfect for both floors and walls.

- MODERN ACCENTS
 - 1 x 24 long linear accents suitable for both floor and wall applications
 - Features metallic visuals with a variety of designs in satin and unpolished finishes
- ELEVATED DESIGN
 - These coordinating accents take neutral and monochromatic designs to the next level
 - Longer linear decorative accents work perfectly with large-format floor tiles

 TRU-EDGE

 CERTIFIED
PORCELAIN
TILE
0.5% or less water absorption

DECORATIVE ACCENT – DIAMOND & DASH



DIAMOND SHIMMER SILVER EO01 – SATIN FINISH



DASH SHIMMER SILVER EO01 – SATIN FINISH



DIAMOND GLIMMER GOLD EO02 – SATIN FINISH



DASH GLIMMER GOLD EO02 – SATIN FINISH

DECORATIVE ACCENT – STRIPE



STRIPE LIGHT GREY EO03 – UNPOLISHED



STRIPE MEDIUM GREY EO04 – UNPOLISHED



STRIPE DARK GREY EO05 – UNPOLISHED

DECORATIVE ACCENT – HEX



HEX LIGHT GREY EO03 – UNPOLISHED



HEX MEDIUM GREY EO04 – UNPOLISHED




HEX DARK GREY EO05 – UNPOLISHED

EMBOLD™

GLAZED PORCELAIN

SIZES

		Thickness	Pieces per Carton
	1 x 24 Decorative Accent (1-1/4" x 23-1/4") (3.30 cm x 59.00 cm)	3/8"	8

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.


OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	
Pool Linings	

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Medium (V2)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information, visit daltile.com/information/TestResults.

NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DAL TILE.COM



7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (8/16)