

# Create Walls to Remember

Festiva™ makes it effortless to create eye-catching designs. Vibrant colors and multiple sizes are hallmarks of this series. Festiva's palette includes over twenty comprehensive colors which coordinate with our Natural Hues floor tile.

- DYNAMIC DESIGN OPPORTUNITIES
  - Comprehensive palette that includes over 20 vibrant colors
  - Colors coordinate with the Natural Hues for added design options
- AMPLE OPTIONS
  - Six wall tile sizes ranging from 3 x 6 to 9 x 12
  - Wide selection of coordinating trim available

#### WALL

USAGE







































LOW HIGH





FINISHES: MATTE | GLOSSY

## **WALL TILE**

















#### SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
9 x 12 Wall Tile	(9" x 12") (22.70 cm x 30.30 cm)	5/16"	11.25	15
6 × 6 Wall Tile	(6" x 6") (15.20 cm x 15.20 cm)	5/16"	12.50	50
4-1/4 x 12-3/4 Wall Tile	(4-1/4" x 12-7/8") (10.88 cm x 32.76 cm)	5/16"	10.64	28
4-1/4 x 8-1/2 Wall Tile	(4-1/4" x 8-9/16") (10.88 cm x 21.82 cm)	5/16"	10.63	42
4-1/4 x 4-1/4 Wall Tile	(4-1/4" x 4-1/4") (10.80 cm x 10.80 cm)	5/16"	12.50	100
3 x 6 Wall Tile	(3" x 6") (7.60 cm x 15.20 cm)	5/16"	12.50	100

## **APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	✓
Pool Linings	N/A	<b>√</b> *

A DCOF value of  $\geq$ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest $^{"}$ , visit daltile.com/DCOF.

#### APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

#### INSTALLATION

Grout Joint Recommendation	Shade Variation
Wall: 1/16" Wall 4 x 12: 1/16" (when used in a staggered brick-joint pattern; overlap should not exceed 33%)	Low (V1)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0

For additional information on test results, visit us at: daltile.com/information/TestResults.

#### NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.





All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



<sup>\*</sup>  $4-1/4 \times 4-1/4$ ,  $3 \times 6$ , and  $6 \times 6$  wall tile only



## TRIM


	Туре	Number	Size	Pieces/ Carton
	Wall Bullnose	S-44C9 (12-3/4" side)	4-1/4 x 12-3/4	28
	Wall Bullnose	S-4309 (9" side)	3 x 9	54
	Wall Bullnose	S-4489 (8-1/2" side)	4-1/4 x 8-1/2	42
	Wall Bullnose	S-4849 (4-1/4" side)	4-1/4 x 8-1/2	42
	Wall Bullnose	S-4269	2 x 6	100
	Wall Bullnose	S-4369 (6" side)	3 x 6	100
	Wall Bullnose	S-4449	4-1/4 × 4-1/4	100
	Wall Bullnose	S-4639 (3" side)	3 x 6	100
	Wall Bullnose	S-4669	6 x 6	50
	Wall Bullnose	S-4C49	4-1/4 x 12-3/4 (4-1/4" side)	28
	Wall Bullnose Corner	SN-4309	3 x 3	32
	Wall Bullnose Corner	SN-4269	2 x 2	25
	Wall Bullnose Corner Left or Right	SCR/L-4489	4-1/4 × 8-1/2	42
	Wall Bullnose Corner Left or Right	SCR/L-44C9	4-1/4 x 12-3/4	28
	Wall Bullnose Corner Left or Right	SCR/L-4369	3 x 6	100
	Wall Bullnose Corner	SCRL-4449	4-1/4 × 4-1/4	100
	Wall Bullnose Corner	SCRL-4669	6 x 6	50
	Radius Bullnose	A-4200	2 x 6	100
0	Radius Outside Corner	AN-4200	2 x 2	20
0	Radius Bullnose	A-4402	4-1/4 × 4-1/4	84
	Radius Bullnose Corner	AN-4402	4-1/4 × 4-1/4	30
	Cove Base	A-3401	4-1/4 × 4-1/4	84
	Cove Base Corner Left or Right	SCR/L-3401	4-1/4 × 4-1/4	30
	Cove Base	A-3601	6 x 6	44
	Cove Base Corner Left or Right	ACR/L-3601	6 x 6	20
	Cove Base	A-3361	3 x 6	36
	Cove Base Corner Left or Right	SCR/L-3361	3 x 6	36
	Quarter Round	A-106	3/4 x 6	152
0	Quarter Round Outcorner	AC-106	3/4 x 6	120
0	Sanitary Cove Base	S-3419T	4-1/4 x 6	60

## TRIM - CONTINUED

Туре	Number	Size	Pieces/ Carton
Sanitary Cove Base Corner Left or Right	SCR/L-3419T	4-1/4 x 6	20
Sanitary Cove Base	S-3619T	6 x 6	40
Sanitary Cove Base Corner Left or Right	SCR/L-3619T	6 x 6	20
Flat Top Cove	A-3481	4-1/4 x 8-1/2	40
Flat Top Cove	A-34C1	4-1/4 × 12-3/4	40
Flat Top Cove Corner Left or Right	SCR/L-3601	6 x 6	20

## SURFACE TRIM


4-1/4 x 4-1/4 Typical Installation\*




\*Opposite not shown

## **CONVENTIONAL TRIM**

4-1/4 x 4-1/4 Typical Installation\*









7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

