



MONOCHROMATIC
LOOK

HARMONIST™
COLORBODY™ PORCELAIN

HARMONIST™

COLORBODY™ PORCELAIN

Powerful Performance With The Look of Luxury

Serenely beautiful, yet tremendously strong and durable, Harmonist™ is a study in contrasts. With its fashionably luxurious look, you would never guess that it can withstand the toughest stains and even frost. Evenly colored throughout its porcelain body, Harmonist will retain its magnificence for years. Available in a range of colors and a matte surface finish.

• STRONG DESIGN

- Organic design inspired by warm sand
- Technical ColorBody™ porcelain for commercial applications

• BEAUTIFUL FINISH

- Available in a matte surface
- Coordinating trim available for those finishing touches

• SPECIAL ORDER STRUCTURES

- Two colors available in Line & Roccia structures
- Perfect for exterior floors

MONOCHROMATIC LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC



LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

Cover photo features Harmonist™ Aura on the floor.
Above photo features Harmonist™ Composure on the floor.

SIZES:



FINISHES: MATTE

SOLID FLOOR TILE



SERENE HM20 (1)



TRANQUIL HM21 (1)



BLISS HM22 (1)



COMPOSURE HM23 (1)



AMBIANCE HM24 (1)



AURA HM25 (1)



DESTINY HM26 (1)



PROMISE HM27 (1)




HAVEN HM28 (1)



POISE HM29 (2)



CELESTIA HM30 (2)



RHYTHM HM31 (2)



AMITY HM32 (3)



SERENADE HM33 (3)




PEACE HM34 (3)




REPOSE HM35 (3)

LINE FLOOR TILE
(Available in 8.4mm & 12.0mm Thickness)*



COMPOSURE HM23 (1)



AMBIANCE HM24 (2)

ROCCIA FLOOR TILE
(Available in 8.4mm & 12.0mm Thickness)*



COMPOSURE HM23 (1)



AMBIANCE HM24 (2)

* **SPECIAL ORDER STRUCTURES** – Longer lead times on special order tile.
(1), (2) and (3) indicate price groups. (1) being the least expensive.



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT™
*Not Applicable to Mesh-Mounted Tiles









CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile	(11-13/16" x 23-5/8") (30.00 cm x 60.00 cm)	3/8"	11.64	6
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	12 x 12* Floor Tile Line & Roccia Structure	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	12 x 12* Floor Tile Line & Roccia Structure	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	7/16"	14.55	15
	8 x 8* Floor Tile Line & Roccia Structure	(7-7/8" x 7-7/8") (20.00 cm x 20.00 cm)	5/16"	12.92	30
	8 x 8* Floor Tile Line & Roccia Structure	(7-7/8" x 7-7/8") (20.00 cm x 20.00 cm)	7/16"	12.92	30

* Special Order Only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	




A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.


* Line & Roccia structures only

TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	S-44C9	4 x 12	38
	Cove Base	S-36C9TP	6 x 12	28
	Cove Base Outcorner	SC-36C9TP	1 x 6	10

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)	 Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.