

3.0mm | 8 mil

HARPER'S PLACE™

FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED

PROSERIES™

LUXURY VINYL FLOORING

 daltile



SuperGuard™
REINFORCED SHIELD

3.0mm | 8 mil

HARPER'S PLACE™

FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED

HARPER'S PLACE™

Designed with the modern metropolitan in mind, Harper's Place™ is fabricated with noise-reducing technology to preserve an atmosphere of tranquility amidst the bustle of city life. This luxury vinyl flooring is available in a wide variety of shades, spanning from cool to warm tones and all offered in a lengthy 7.5" x 48.5" plank. Built with SuperGuard™ to withstand everyday foot traffic, Harper's Place maintains its elegance long-term.

LUXURIOUS DESIGN

- 7.5" x 48.5" wood look planks
- Cool to warm tone color palette
- Flexible Glue Down with acoustical pad attached
- Embossed for realistic look and feel
- Built-in solid IXPE underlayment pad that resists mold and mildew
- 3.0 mm Thickness

PROVEN DURABILITY

- SuperGuard™ Technology
- 8 mil wear layer for heavy foot traffic
- 100% Waterproof
- 100% Virgin Vinyl
- Limited 20 Year Residential Warranty
- Limited 3 Year Multifamily Warranty



Cover photo features Harper's Place™ Tudor 7-1/2 x 48-1/2 plank on the floor and ONE Quartz Surfaces® Monochromatic Look, Woven Wool on the countertop.
Above photo features Harper's Place™ Ranch 7-1/2 x 48-1/2 plank on the floor, Brickwork™ Terrace 4 x 8 tiles on the backsplash, and Natural Stone Granite Bravo Presto on the countertop.

3.0mm | 8 mil

HARPER'S PLACE™

FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED

SIZES:



7-1/2 x 48-1/2
Plank

7.5 x 48.5 WOOD LOOK PLANKS



COTTAGE
HP40



CRAFTSMAN
HP38*



COLONIAL
HP31*



TOWNHOUSE
HP30*



RANCH
HP32



FRENCH
COUNTRY HP33



RUSTIC
HP34



TUDOR
HP35*



BUNGALOW
HP36



FARMHOUSE
HP37*



VICTORIAN
HP39

* SPECIAL ORDER COLOR

3.0mm | 8 mil

HARPER'S PLACE™

FLEXIBLE GLUE DOWN WITH ACOUSTICAL PAD ATTACHED



NOISE REDUCING



EASY TO CLEAN



100% WATERPROOF



100% VIRGIN VINYL

SPECIFICATIONS

Product Type:	Flexible Glue Down with acoustical pad attached
Installation:	Flexible Glue Down
Thickness:	3.0 mm
Wear Layer:	8 mil (0.2032 mm)
Finish:	SuperGuard™ Technology
Size:	7-1/2" W x 48-1/2" L Plank
Underlayment:	Pad Attached; 1.0 mm IXPE
Bevel:	No Bevel
Embossing:	Embossed
Plank Variation:	5 Unique Planks
Sq. Ft./Carton:	40.64
Pieces/Carton:	16 pcs/carton
Weight	1.89 lbs per pc / 30.24 lbs per carton
Warranty:	Limited 20 Year Residential Warranty Limited 3 Year Multifamily Unit Warranty

Installation Advisory: Glue Down LVF must be installed using ProSeries by Daltile Adhesive. See daltile.com/LVF for more recommended installation and adhesive information.

Stocking Platform: 3 mm, 8 mil

Special order Platform: Additional Platforms available on special order. Minimum quantities apply. Contact your Daltile representative for additional information.

PERFORMANCE & CHARACTERISTICS

Construction:	Commercial Grade Luxury Vinyl Flooring; 100% Virgin Vinyl
Classification:	ASTM F1700-Class III, Type A-Smooth, Type B-Embossed
Squareness:	ASTM F2421 - Passes - $\pm 0.010"$ max
Size and Tolerance:	ASTM F2421 - Passes - Plank Length ≥ 48 in. ± 0.080 in. (2 mm)
Thickness:	ASTM F386 - Passes - ± 0.118 inches
Flexibility:	ASTM F137 - Passe - 1 in. (25.4-mm) mandrel, no crack or break
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in./lin. Ft (0.51mm/ 305 mm) maximum
Residual Indentation:	ASTM 1914 - Passes - Average < 8.0 %
Resistance To Chemicals:	ASTM F925 - Passes - ≤ 1 Slight Change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 8$

NOTES

See daltile.com/LVF for recommended installation and care guidelines.



CERTIFIED BY
SCS Global Services

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com/LVF

PROSERIES™
LUXURY VINYL FLOORING

daltile

©2023 Dal-Tile, LLC (9/23)