



STONE LOOK

FLOOR | WALL
HEATHLAND™
GLAZED CERAMIC

 **daltile®**
IMAGINE WHAT'S POSSIBLE™

FLOOR | WALL

HEATHLAND™

GLAZED CERAMIC

Rustic Style That Has a Multitude of Uses

Heathland™ glazed ceramic tile offers homeowners, designers, builders and architects the rustic look they have been seeking in an array of colors and sizes. It is available in a full floor and wall package with coordinating trim options and versatile decorative accents. Suitable for both commercial and residential use, Heathland will add natural character to any décor.

- RUSTIC VERSATILITY

- Natural character and color palette add rustic look to space
- Suitable for both commercial and residential use

- COMPLETE OFFERING

- Offered in five colors and multiple floor, wall and mosaic sizes
- Coordinating trim and decorative accents available.

STONE LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



C.G.
CRADLE TO CRADLE



LOW HIGH

SPECIAL FEATURES

SEE CHARTS FOR FULL
PRODUCT DETAILS

Above and Cover photos feature Ashland 12 x 12 on the floor.

SIZES:



FINISHES: MATTE

FLOOR TILE




WHITE ROCK HL01



RAFFIA HL02



AMBER HL03



EDGEWOOD HL04



ASHLAND HL05

WALL TILE




WHITE ROCK HL01*




RAFFIA HL02*



AMBER HL03*



EDGEWOOD HL04*



ASHLAND HL05

*9 X 12 AND 3 X 6 WALL TILE AVAILABLE IN COLORS HL01, HL02, HL03 AND HL04 ONLY.

MOSAICS



SUNRISE BLEND HL07
 2 X 2 MOSAIC
 (50% WHITE ROCK HL01 AND 50% RAFFIA HL02)



SUNSET BLEND HL08
 2 X 2 MOSAIC
 (30% AMBER HL03, 30% EDGEWOOD HL04, 20%
 ASHLAND HL05, 20% SAGE HL06)



SLIP RESISTANT



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes











FIRE-RESISTANT



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	18 x 18 Floor Tile	(17-11/16" x 17-11/16") (45.01 cm x 45.01 cm)	5/16"	17.44	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	15.52	16
	9 x 12 Wall Tile ■	(9" x 12") (22.91 cm x 30.54 cm)	5/16"	11.25	15
	6 x 6 Wall Tile	(6" x 6") (15.20 cm x 15.20 cm)	5/16"	12.50	50
	3 x 6 Wall Tile ■	(3" x 6") (7.66 cm x 15.33 cm)	5/16"	12.50	100
	2 x 2 Mosaic (Dot-mounted)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12
	4 x 12 Floor Border	(4-1/16" x 11-3/4") (10.30 cm x 29.90 cm)	5/16"	--	10
	2 x 10 Wall Border	(1-7/8" x 10") (4.76 cm x 25.80 cm)	5/16"	--	10

■ Available in colors HL01, HL02, HL03 and HL04 only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓†
Wet & Level – Interior Floor	≥ 0.42	✓†
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓**
Pool Linings	N/A	✓***


A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

- † Wall tile not suitable for this application.
- * Mosaic tile only
- ** Floor, 3 x 6 and 6 x 6 wall and mosaic tile only
- *** 3 x 6, 6 x 6 wall and mosaic tile only

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) Wall: 1/16" Mosaic: 1/8"	 High (V3)



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.



TRIM

Type	Number	Size	Pieces/ Carton
Floor Bullnose	P43C9	3 x 12	22
Cove Base	P36C9TB	6 x 12	22
Cove Base Outcorner	PC36C9TB	1 x 6	15
Wall Bullnose	S4669	6 x 6	50
Wall Bullnose Corner	SCRL4669	6 x 6	50
Wall Bullnose (6" side)	S4269	2 x 6	100
Wall Bullnose Corner	SN4269	2 x 2	25
Radius Bullnose	A4200	2 x 6	100
Radius Bullnose Corner	AN4200	2 x 2	20
Wall Bullnose (9" side) ■	S4309	3 x 9	54
Wall Bullnose Corner ■	SN4309	3 x 3	32
Counter Rail ■	26CRWL	2 x 6	36
Counter Rail Corner ■	22CRCN	2 x 2	24
Quarter Round ■	A106	1 x 6	152
Quarter Round Corner ■	UC106	1 x 1	40
Mosaic Bullnose	S886	2 x 2	108

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove corner trim are suitable for non-freezing climates only.

■ Available in colors HL01, HL02, HL03, and HL04 only.

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltille.com.

