



METALLIC LOOK













































SEE CHARTS FOR FULL PRODUCT DETAILS.

Cover photo features Iridescent Isles™ Cove, 2 x 9 on the wall, ONE Quartz Surfaces® Outer Banks on the fireplace bench

and Indoterra™ White Desert, 6 x 24 on the floor.

Above photo features Iridescent Isles™ Treasure, 2 x 9 on the exterior wall & inset, Indoterra™ Riverbed, 24 x 48 on the boutique floor and Assemble™ Magistrate, 30/x 30 on the exterior floor.

IRIDESCENT ISLES™

GLAZED PORCELAIN WALL TILE



2 x 9 Wall Tile

COLOR PALETTE













SEASHELL

COVE

SEAWEED

ANCHOR

GLAZED PORCELAIN WALL TILE





SEASHELL IR20





TREASURE IR25

HARBOR IR24



ANCHOR IR22

SEAWEED IR23













IRIDESCENT ISLES™

GLAZED PORCELAIN WALL TILE

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
2 x 9 Wall Tile	2-1/4" x 9-1/2" (6.00 cm x 24.60 cm)	3/8"	5.72	36

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors - Standard Center Drain (Residential or Light Commercial)	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.60	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	~

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation	
Wall: 1/8"	Medium (V2)	

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com







All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com









