



DECORATIVE

LINERS & CHAIR RAILS

GLAZED CERAMIC

 **daltile**[®]
IMAGINE WHAT'S POSSIBLE™



Cover and above photos feature Semi-Gloss™ Spa 6 x 6 wall tile, Artisan Brown and Almond 1 x 6 and 1/2 x 6 flat liners, and Keystones™ Uptown Taupe and Semi-Gloss™ Spa 2 x 2 on the wall.

Add in the Finishing Touches

Looking for a way to enhance a wall design? Try a Daltile liner or chair rail. Use these decorative wall accents, available in a wide assortment of colors, to add a complementing element to any design.

- **ACCENTUATING DÉCOR**
 - Decorative wall accents, ideal for enhancing wall and backsplash designs
 - Coordinates with several other Daltile products, such as Semi-Gloss™ and Matte™ and Rittenhouse Square™
- **EXPANSIVE DESIGN**
 - Three styles available in an assortment of colors
 - When coordinated with other Daltile series, the design options are almost endless



**PRE-CONSUMER
RECYCLED MATERIALS**



REVEAL IMAGING®


All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

DECORATIVE
LINERS & CHAIR RAILS
GLAZED CERAMIC


SEMI-GLOSS™



WHITE K101***




ARCTIC WHITE 0190*



WHITE 0100*



BISCUIT K175*



ALMOND 0135***



ALMOND K165***




LUMINARY GOLD
0142**



VERMILLION ODM1**




COBALT DM14**



SUEDE GRAY 0182**




ARTISAN BROWN
0144**




BLACK K111*

MATTE™



MATTE ARCTIC
WHITE 0790***



MATTE
ALMOND X735***



MATTE
BISCUIT K775***



MATTE
BLACK K711***




* Available in liner and chair rail
** Available in liner only
*** Available in chair rail only

DECORATIVE

LINERS & CHAIR RAILS

GLAZED CERAMIC

SIZES

			Thickness	Number	Pieces per Carton
	1 x 6 Flat Top Liner	(1" x 6") (2.50 cm x 15.20 cm)	5/16	161	20
	1/2 x 6 Flat Top Liner	(1/2" x 6") (1.30 cm x 15.20 cm)	5/16	1/26	20
	2 x 6 Chair Rail	(2" x 6") (5.20 cm x 15.20 cm)	5/16	26CR	80


APPLICATIONS

	Suitable
Floors	
Walls/Backsplashes	✓
Countertops	
Pool Linings	✓

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16"	 Low (V1)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 20%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information, visit daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.

7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (4/17)