

MESMERIST™

GLAZED CERAMIC

Spellbound Style

Mesmerist^{**} captivates with six alluring colors revealing the look of handmade ceramic tile. The luring beauty demonstrated by Mesmerist's variation in color and structure gives you a captivating space. Bewitching rectangular and hexagonal wall tiles with an arabesque mosaic add a shimmering touch of mystery to your enchanting design.

BECKONING BRILLIANCE

- Uneven edges, undulating structure and variation in color from piece to piece creates beguiling designs
- Six captivating colors enhance its hypnotizing, handmade look

ENCHANTING OPTIONS

- Rectangular wall tile offered in 3x12 and 3x6
- 4" hexagon creates wonderous visuals
- Popular arabesque mosaic for cultured detail
- Jolly can be used as a liner, trim or decorative accent

WALL

USAGE

































FOR ALL PRODUCTS
IN THIS SERIES. SEE
CHARTS FOR FULL
PRODUCT DETAILS.



Make tolay fresh and beautiful







3 x 12 Wall Tile

3 x 6 Wall Tile

4" Hexagon Wall Tile



INISHES: GLOSSY

COLOR PALETTE













WALL TILE



SPIRIT MM30



WHIMSY MM34



TRANCE MM31







CHARM MM32



MYSTIQUE MM35

4" HEXAGON WALL TILE



SPIRIT MM30



TRANCE MM31



CHARM MM32

CHARM MM32





ALLURE MM33



ARABESQUE MOSAIC













SPIRIT MM30 TRANCE MM31



DENTPROOF

FIRE-RESISTANT

WHIMSY MM34



ALLURE MM33

MESMERIST™

GLAZED CERAMIC

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	3 x 12 Wall Tile	(3" x 11-13/16") (7.50 cm x 30.00 cm)	5/16"	12.00	48
	3 × 6 Wall Tile	(2-15/16" x 5-7/8") (7.46 cm x 14.79 cm)	5/16"	12.00	100
\bigcirc	4" Hexagon Wall Tile	(4-1/4" x 4-7/8") (10.92 cm x 12.40 cm)	5/16"	3.00	30
	Arabesque Mosaic (Dot-mounted)	(11" x 12" Sheet) (27.94 cm x 30.48 cm Sheet)	1/4"	7.40	10

APPLICATIONS

Target DCOF wet	Suitable
N/A	
≥ 0.42	
≥ 0.42	
≥ 0.60	
≥ 0.65	
N/A	~
N/A	
N/A	√ *
	DCOF wet N/A ≥ 0.42 ≥ 0.42 ≥ 0.60 ≥ 0.65 N/A N/A

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed. *Mosaic tile only





All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

TRIM

 Туре	Number	Size	Pieces/ Carton
12" Jolly	S1/212J	1/2 x 11-15/16	12

INSTALLATION

Grout Joint Recommendation	Shade Variation		
Wall: 3 x 6 & 3 x 12: 1/8" 4" Hexagon: 1/16"	Random (V4)		
Mosaic: 1/8"			

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result	Mosaic Result
Water Absorption	C373	< 20.0%	< 3.0%
Breaking Strength	C648	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	4.0 - 6.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.







