



FLOOR

**METAL FUSION™**  
COLORBODY™ PORCELAIN

 **daltile®**  
IMAGINE WHAT'S POSSIBLE™



Cover photo features Metal Fusion™ Bronzed Copper 8 x 24 and Stainless Steel 24 x 24 on the floor.  
Above photo features Metal Fusion™ Bronzed Copper 8 x 24 on the floor.

## Amplify your Contemporary Style with the Look of Metal

Add urban industrial style to your space with Metal Fusion. This sophisticated porcelain collection features metallic flecks on its surface to create a realistic organic look. Metal Fusion is available in three classic metallic colors and four modular sizes, including large-format. With its authentic design and versatile sizing, Metal Fusion makes it easy to give any room a sleek, modern look.

- REALISTIC DESIGN
  - Contemporary floor tile with metallic look
  - Adds high-end urban style to the space
  - Features metallic flecks on surface to create its realistic organic look
- CHIC VERSATILITY
  - Offered in three classic metallic colors
  - Coordinating trim and large-format sizes available



**PRE-CONSUMER RECYCLED MATERIALS**



**TRU-EDGE**

All or select items within this series meet the requirements for these qualifications. For more product information, visit [daltile.com](http://daltile.com)

CERTIFIED  
**PORCELAIN**  
TILE  
© 2014 BY DALL-WATKINS ASSOCIATES

*Professional*  
TILE SOLUTIONS

FLOOR TILE



BRONZED COPPER P452



STAINLESS STEEL P450



ZINC OXIDE P451

FLOOR

# METAL FUSION™

COLORBODY™ PORCELAIN

## SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 24 Floor Tile (Light Polished)	(24" x 24") (61.00 cm x 61.00 cm)	3/8"	16.04	4
	16 x 24 Floor Tile (Light Polished)	(15-15/16" x 24") (40.50 cm x 61.00 cm)	3/8"	10.66	4
	16 x 16 Floor Tile (Light Polished)	(15-15/16" x 15-15/16") (40.50 cm x 40.50 cm)	3/8"	14.10	8
	8 x 24 Floor Tile (Light Polished)	(7-15/16" x 24") (20.30 cm x 61.00 cm)	3/8"	10.66	8

## FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

## OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

## APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

**Due to the metallic granules used on the surface of the tile, it is extremely important to ensure that the tile does not come in contact with any abrasive agents or chemicals.**

## TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	S-43D9	3 x 16	30

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern and/or when tile with a length 15" or greater is installed in a staggered brick-joint pattern. Overlap should not exceed 33%)	 High (V3)

## TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 450 lbs
Scratch Hardness	MOHS	6.0
Chemical Resistance	C650	Resistant

## NOTES

**Manufacturer Advisory:** These tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at [daltile.com/Factors](http://daltile.com/Factors).



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: [GET.DALTILE.COM](http://GET.DALTILE.COM)



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (1/17)