

# MULTITUDE™

GLAZED CERAMIC

## A Marvelous Canvas of Color and Texture

With a subtle finish and pronounced patterns, Multitude<sup>™</sup> tile gives you a different look at every glance. It differentiates itself with a combination of rich colors and a 3-D pinstriped graphic that underlies flat, hexagonal and wave patterns. Offered in five vibrant colors and a large modern size, this design adds depth and character to any room.

- MODERN DESIGN
  - Alluring textures provide visual depth and interest
  - Customize your wall design with this series of distinctive, coordinating combinations
- ENDLESS FLEXIBILITY
  - Offered in large modern 12 x 24 tile size
  - Five-color palette easily coordinates with any room
  - 3-D pinstripe graphic underlies flat,hexagonal and wave patterns that continue seamlessly from one tile to the next

WALL

USAGE







































SEE CHARTS FOR FULL PRODUCT DETAILS

( SIZES:

12 x 24 Wall Tile

FINISHES: SATIN | TEXTURED





WALL TILE (Shown in Wave)



WALL TILE (Shown in Hexagon)



ORIGAMI WHITE MU16 ORIGAMI WHITE MU16



of tile

of tile

MODERN KHAKI MU17










URBAN GREY MU18





NOSTALGIC BLUE MU19







DOMINO BLACK MU20











STAINPROOF DENTPROOF SCRATCH-RESISTANT

## MULTITUDE™ GLAZED CERAMIC

### SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
12 x 24 Wall Tile	(11-3/4" x 23-3/4") (29.90 cm x 60.42 cm)	3/8" (9.3 mm)	15.52	8

#### **APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	<b>~</b>
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

## APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

## JOLLY TRIM - SOLID COLORS

ORIGAMI WHITE MU21

MODERN KHAKI MU22

URBAN GREY MU23

NOSTALGIC BLUE MU24

DOMINO BLACK MU25

## TRIM

Туре	Number	Size	Pieces/ Carton
12" Jolly	S-1/212J	1/2 x 11-15/16	12

## INSTALLATION

Grout Joint Recommendation Shade Variation	on
--	----

 $\textbf{Wall:}\ 1/8"$  (when used in a staggered brick-joint pattern; overlap should not exceed 33%)



#### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

## NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.





