



FLOOR

PORADA™

GLAZED PORCELAIN with REVEAL IMAGING®

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature Rich Brown 13 x 20 field tile in a staggered brick-joint pattern

Outstanding Alternative to Slate

Transform any room with the unique visionary design of Porada™. Its beautifully stylized texture looks and feels like natural slate. Porada has a bold color palette that compliments both traditional and modern homes. With its slate appearance and ease of maintenance, Porada is an exquisite choice that is sure to make a grand statement.

- DESIGN & STYLE
 - Obtain a unique slate look with a concrete influence
 - Subtle shimmer effect and vibrant color palette add character and visual interest
- SIMPLE UPKEEP
 - Durability and easy care make this tile a low-maintenance choice



**PRE-CONSUMER
RECYCLED MATERIALS**



MADE IN THE U.S.A.



REVEAL IMAGING®

All or select items within this series are made in the USA. For more information, visit daltile.com/Porada.

**CERTIFIED
PORCELAIN
TILE**
© 8% or less water absorption

FIELD TILE



SUBTLE GREY PR33



SOFT TAUPE PR31



RICH BROWN PR32



DEEP GREY PR34

FLOOR

PORADA™

GLAZED PORCELAIN with REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	20 x 20 Field Tile	(19-3/4" x 19-3/4") (50.20 cm x 50.20 cm)	5/16"	16.26	6
	13 x 20 Field Tile	(13-1/8" x 19-3/4") (33.30 cm x 50.20 cm)	5/16"	12.60	7
	13 x 13 Field Tile	(13-1/8" x 13-1/8") (33.30 cm x 33.30 cm)	5/16"	16.66	14

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.



OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.


TRIM

	Type	Number	Size	Pieces per Carton
	Floor Bullnose	P-43E9	3 x 13	30
	Cove Base†	P-36E9T	6 x 13	22
	Cove Base Outcorner†	PC-36E9T	1 x 6	15

† Cove base and cove base outcorner are clay body ceramic suitable for non-freezing climates only.

Floor bullnose, cove base, and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" (overlap should not exceed 33% when installing in a staggered brick-joint pattern; when multiple sizes are installed in a modular pattern, please specify same size caliber at time of order)	 Random (V4)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	4

For additional information, visit daltile.com/information/TestResults.

NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DAL TILE.COM



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (7/16)