



STONE LOOK

SEVERINO™  
GLAZED CERAMIC

 daltile®  
IMAGINE WHAT'S POSSIBLE™



**SEVERINO™**  
GLAZED CERAMIC

## Contemporary Interpretation of Established Stone Looks

Taking its cue from the tumbling cliffs of the Amalfi Coast, Severino is a beautiful mix of travertine and marble looks designed to add visual warmth with its natural beauty. Severino differentiates itself with a rich, stone graphic and an organic color palette. Offered in four colors and six versatile sizes, including a 2 x 2 pressed mosaic and 2-inch octagonal mosaic, Severino exhibits relaxed sophistication.

- **IMAGINATIVE DESIGN**

- Contemporary take on a classic stone look in four natural colors
- Smooth travertine and marble graphics achieved through Reveal Imaging® technology

- **UNIFYING COMBINATIONS**

- Decorative wall accent, mosaics and trim coordinate with floor and wall tile
- Organic color palette that harmonizes any space

Cover photo features Severino™ Cenere Fog 18 x 18 floor tile on the floor, Cenere Fog 10 x 14 wall tile and 2 x 2 mosaic on the wall. Above photo features Severino™ Cenere Fog 18 x 18 floor tile on the floor and Cenere Fog 2 x 2 mosaic on the wall.

### STONE LOOK

### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER  
FLOOR



EXTERIOR  
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN  
THE U.S.A.



LARGE  
FORMAT



MOSAIC/  
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



C<sup>G</sup>



LOW HIGH

SEE CHARTS FOR FULL  
PRODUCT DETAILS

### SPECIAL FEATURES




SIZES:



18 x 18  
Floor Tile



12 x 24  
Floor Tile



12 x 12  
Floor Tile



10 x 14  
Wall Tile



2 x 10  
Deco Wall Accent



2 x 2  
Mosaic



2 x 2 Octagon  
with 1" Mosaic

FINISHES: MATTE

FLOOR & WALL TILE



VENTO BREEZE SV96



ARIA SAND SV97



CENERE FOG SV98




TERRA BRUNO SV99


2" OCTAGON & 1" DOT MOSAIC



VENTO BREEZE SV96



ARIA SAND SV97



CENERE FOG SV98



TERRA BRUNO SV99

2 x 2 MOSAIC



VENTO BREEZE SV96



ARIA SAND SV97



CENERE FOG SV98



TERRA BRUNO SV99

DECORATIVE ACCENTS



CESTINO FRESCO SV94  
(COORDINATES WITH SV96 & SV98)



CESTINO CALDO SV95  
(COORDINATES WITH SV97 & SV99)



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT\*  
\*Applicable to products with Matte and Textured Finishes










FIRE-RESISTANT\*  
\*Not Applicable to Mesh-Mounted Mosaics



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	18 x 18 Floor Tile	(17-1/2" x 17-1/2") (44.45 cm x 44.45 cm)	5/16"	17.04	8
	12 x 24 Floor Tile	(11-9/16" x 23-3/8") (29.40 cm x 59.30 cm)	3/8"	15.04	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	10 x 14 Wall Tile	(9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	2 x 10 Decorative Wall Accent	(1-3/4" x 9-7/8") (4.50 cm x 24.90 cm)	1/4"	N/A	6
	2 x 2 Mosaic (Dot-mounted on 12" x 24" Sheet)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12
	2" Octagon with 1" Dot Mosaic (Dot-mounted on 12" x 12" Sheet)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4"	10.00	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest®, visit [daltille.com/DCOF](https://daltille.com/DCOF).

APPLICATION NOTES:






Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

\* Mosaic tile only.



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltille.com](https://daltille.com).

TRIM

	Type	Number	Size	Pieces per Carton
	Floor Bullnose ■	P43C9	3 x 12	22
	Wall Bullnose	S4310 (10" side)	3 x 10	54
	Wall Bullnose Corner	SN4310	3 x 3	32
	Quarter Round	A106	1 x 6	152
	Quarter Round Corner	UC106	1 x 1	40

■ Floor bullnose is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
----------------------------	-----------------

**Floor:** 3/16" (overlap should not exceed 33% when installing tile with a length of 15" or greater in a staggered brick-joint pattern)



**Wall:** 1/16";

**Mosaics:** 1/8"

TEST RESULTS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information, visit [daltille.com/information/TestResults](https://daltille.com/information/TestResults).

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms ③	All Residential / Light Commercial
2	All Residential Areas 4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Special consideration must be given when installing tiles greater than 15 inches. Please refer to [daltille.com/LargeTiles](https://daltille.com/LargeTiles) for more information.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at [daltille.com/Factors](https://daltille.com/Factors).

**Manufacturer Advisory:** These tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1