

CONCRETE LOOK

SIERRA TM GLAZED CERAMIC

a daltile IMAGINE WHAT'S POSSIBLE

Create a Room that Makes a Statement

If you're looking for a tile that's as attractive as it is durable, try Daltile's, Sierra™ series. Subtle tone variations and a soft matte glaze create a beautiful

- Subtle tone variations adds a beautiful visual effect to room
- Features a neutral color palette that easily coordinates into multiple designs
- MULTIFACETED BEAUTY
 - Design includes five colors in a 12 x 12 floor tile

CONCRETE LOOK







































12 x 12 Floor Tile

FINISHES: MATTE

COLOR PALETTE











GLAZED CERAMIC FLOOR TILE








RAINIER 1500





BLACK 2011













SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	15.52	16

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest $^{"}$, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

TRIM

Туре	Number	Size	Pieces/ Carton
Bullnose	P-43C9	3 x 12	22

INSTALLATION

Grout Joint Recommendation	Shade Variation	
3/16"	Low (V1)	

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

FLC	Floor Surface Wear Resistance				
1	Residential Bathrooms	3	All Residential / Light Commercial		

2 All Residential Areas 4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.





