















































STARCASTLE™







Mini Hexagon





Elongated Hexagon Mosaic



Chevron




Diamond Scale Mosaic


TRIANGLE MOSAIC







WONDERSTAR SC77



SUPERNOVA SC78



STARDUST SC79

MINI HEXAGON MOSAIC



CELESTIAL SC75



COMET SC76



WONDERSTAR SC77 SUPERNOVA SC78





STARDUST SC79

LEAF MOSAIC





COMET SC76



WONDERSTAR SC77



SUPERNOVA SC78



STARDUST SC79

ELONGATED HEXAGON MOSAIC



CELESTIAL SC75



COMET SC76



WONDERSTAR SC77 SUPERNOVA SC78 STARDUST SC79



DIAMOND SCALE MOSAIC



CHEVRON MOSAIC



MILKY WAY SC72



SPIRAL GALAXY SC73



GALACTIC SWIRL SC74





MILKY WAY SC72



GALAXY SC73



GALACTIC SWIRL SC74



STAINPROOF





STARCASTLE[™]

GLASS MOSAICS

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	Triangle Mosaic* (Mesh-Mounted)	(12" x 11-3/16") (30.50cm x 28.50cm)	1/4″	11.77	13
	Mini Hexagon Mosaic* (Mesh-Mounted)	(11-5/8" x 11-5/8") (29.50cm x 29.50cm)	1/4″	13.80	15
	Leaf Mosaic* (Mesh-Mounted)	(12-5/8" x 12-1/16") (32.00cm x 30.70cm)	1/4″	14.70	15
	Elongated Hexagon Mosaic* (Mesh-Mounted)	(12-5/8" x 11-7/16") (32.00cm x 29.00cm)	1/4″	13.28	15
	Chevron Mosaic** (Mesh-Mounted)	(13-7/16" x 11-7/8") (34.11cm x 30.20cm)	1/4″	12.75	15
\bigotimes	Diamond Scale Mosaic** (Mesh-Mounted)	(12-1/4" x 9-11/16") (31.10cm x 24.50cm)	1/4″	7.50	15

^{*} Available in SC75, SC76, SC77, SC78 and SC79 colors only.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	/ *
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	✓ **

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods

- * Mini Hexagon and Leaf mosaics only.
- ** Chevron and Diamond mosaics only.





All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

Grout Joint Recommendation	Shade Variation	
1/8"	High (V3)	

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	0.0%
Breaking Strength	C648	> 350 lbs
Scratch Hardness	MOHS	6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

INSTALLATION

Flo	oor Surface Wear Resista		
1	Residential Bathrooms	3	All Residential / Light Commercial*
2	All Residential Areas	4	All Residential / Commercial

^{*} Mini Hexagon and Leaf mosaics only.

NOTES

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. ANSI A137.2 Standards.

For additional information refer to "Factors to Consider" at: daltile. com/Factors.







^{**} Available in SC72, SC73 and SC74 colors only.