



MOSAIC

DECORATIVE
TIGER EYE™
GLASS MOSAICS



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

Create An Exotic Escape

The antique look of glass married with earthy tones create the striking blends included in the Tiger Eye series. Bring intrigue to interior spaces using the Tiger Eye Random Linear mosaics, or add that perfect element of shine with the Tiger Eye Metallic collection. This stunning option for backsplashes and accent walls will transform your space into an exotic escape.

- **STUNNING APPEAL**

- Gorgeously crafted blends of color for a worldly feel
- Unique combination of metallic and glass looks

- **MULTIPLE DESIGN OPTIONS**

- Can be placed vertically or horizontally for additional design possibilities
- Available in several finishes to suit any design space

MOSAIC

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



M^x METAL MESH



LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

Cover photo features Tiger Eye™ Indo Stainless 3" block random mosaic on the wall.
Above photo features Tiger Eye™ Malayan 1 x random linear mosaic on the wall.

SIZES:



Random Linear
Mosaics

FINISHES: GLOSSY

1 X RANDOM LINEAR MOSAIC – GLASS



SUMATRAN TE28



SIBERIAN TE26



BALI TE22



MALAYAN TE25



BENGAL TE27



CASPIAN TE21




INDO TE24



SIMPLICLEAN™

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	1 x Random Linear Mosaics (Mesh-mounted)	(12-3/4" x 11-3/4" Sheet) (32.30 cm x 29.80 cm Sheet)	5/16"	10	10

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

For interior use only. Not suitable for use in wet areas such as shower walls.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

For additional information refer to "Factors to Consider" at daltille.com/Factors.