WOOD LOOK





## FLOOR | WALL **TIMBER GLEN<sup>™</sup>** COLORBODY<sup>™</sup> PORCELAIN

# Contemporary Spin on Rustic Hardwood

Timber Glen provides the character of wood-look with a modern twist. This stylized hand-scraped look captures the rich essence of wood planking in six exquisite natural tones. With its contemporary character and natural elegance, Timber Glen offers a discriminating fashion sense for any room.

- MODERN TAKE ON A POPULAR DESIGN
  - Modern, stylized take on traditional wood-looks
  - Hand-scraped look adds contemporary styling
- NATURAL DESIGN
  - Six lush nature-inspired tones add warmth and richness to space
  - Size and graphic present an authentic wood look

RU-EDG

SEE CHARTS FOR FUL

WOOD

LOOK

## FLOOR | WALL TIMBER GLEN<sup>™</sup> COLORBODY<sup>™</sup> PORCELAIN



FINISHES: MATTE

### FLOOR TILE



THATCH P625



DUNE P620



COCOA P623



ESPRESSO P624











FIRE-RESISTANT

CLIMATEPRO™



WATERPROOF

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.





CHERRY P622

#### FLOOR | WALL

# TIMBER GLEN<sup>™</sup>

COLORBODY<sup>™</sup> PORCELAIN

SIZES				
		Thickness	Sq. Ft./ Carton	Pieces/ Carton
12 x 24 Floor Tile	(11-13/16" x 23-5/8") (30.00 cm x 60.00 cm)	3/8"	11.62	6
6 x 24 Floor Tile	(5-7/8" x 23-5/8") (15.00 cm x 60.00 cm)	3/8"	11.62	12

#### APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	~
Wet & Level – Interior Floor	≥ 0.42	~
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	~
Countertops	N/A	~
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest<sup>™</sup>, visit daltile.com/DCOF.

#### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.



TRIM					
Туре		Number	Size	Pieces/ Carton	
	Bullnose	S-44F9	4 x 24	16	

### INSTALLATION

33%.)

Grout Joint Recommendation	Shade Variation		
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint	Medium (V2)		

#### PERFORMANCE CHARACTERISTICS

pattern; overlap should not exceed

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

#### DURABILITY

Floor Surface Wear Resistance				
1	Residential Bathrooms	3	All Residential / Light Commercial	
2	All Residential Areas	4	All Residential / Commercial	

#### NOTES

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile<sup>®</sup> products and information, visit our website at daltile.com.





