



PENNY ROUND N215 SPECKLED GRAY
1" Penny Round N215 DID 21045 Speckled Gray



PENNY ROUND N216 SPECKLED BLACK
1" Penny Round N216 DID 21046 Black

Please note: Image above displays the graphic design for the custom tile detailed in this document. Samples of actual material are available upon request.

PRE-CONSUMER RECYCLED MATERIALS
 MADE IN THE U.S.A.



FLOOR/WALL
STARBUCKS
UNGLAZED PORCELAIN

STARBUCKS CUSTOM ITEM DESCRIPTION

Color	N215 Speckled Gray
Color	N216 Speckled Black
UOM	Square Foot

CONTACT INFORMATION

Orders & Design: starbucks@daltile.com

SIZE

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
Penny Round (1" x 1" Piece) (1" x 22" Sheet) (28 cm x 55 cm Sheet)	1/4"	21.12	12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Exterior Applications, pool decking, & other wet areas with minimal footwear	≥ 0.55	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

* Mosaics have recurrent grout joints and reflect a DCOF of ≥ 0.55 wet making them suitable for these applications.

DAL-TILE 1-YEAR LIMITED WARRANTY (EXTENDED WARRANTIES AVAILABLE)

Dal-Tile Corporation warrants that manufactured products will be free from defect for a period of one-year from date of purchase. Defect is defined as a shortfall in the product to perform to Dal-Tile specifications as disclosed in product literature, within industry allowable tolerances as set forth in standard, national industry protocols. Dal-Tile provides detailed information in its product literature regarding appropriate tile and stone applications. Failure to comply with recommended applications voids this warranty. **THIS ONE-YEAR EXPRESS WARRANTY IS THE SOLE WARRANTY EXTENDED AND REPLACES ANY STATUTORY WARRANTIES TO THE MAXIMUM EXTENT ALLOWABLE BY LAW.** For full warranty information including implications, exclusions and limitations please visit www.Daltile.com.

THE INFORMATION RELEASED IS A PROPOSAL FOR CLIENT CONSIDERATION PURPOSES ONLY. FINAL TEST RESULTS & PART NUMBERS WILL BE PROVIDED

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	Medium (V2) to Random (V4)

Additional installation recommendations can be found in the current edition TCNA Handbook and/or NTCA Reference Manual

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 300 lbs
Scratch Hardness	MOHS	N/A
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

CARE AND MAINTENANCE

Please refer to the "DalTile Care and Maintenance Guide" available at www.Daltile.com