



TERRA COTTA MC56

Please note: Image above displays the graphic design for the custom tile detailed in this document. Samples of actual material are available upon request.

- POST-CONSUMER RECYCLED MATERIALS**
- PRE-CONSUMER RECYCLED MATERIALS**
- MADE IN THE U.S.A.**
- REVEAL IMAGING®**
- CERTIFIED PORCELAIN™ TILE**
0.5% or less water absorption
- ZEROTOX**
Healthy Homes | Healthy Planet

FLOOR/WALL

MOROCCAN CONCRETE™

COLORBODY™ AND GLAZED PORCELAIN WITH STEPWISE™ TECHNOLOGY

STARBUCKS CUSTOM ITEM DESCRIPTION

Color	MC56 Terra Cotta
UOM	Square Foot

CONTACT INFORMATION

Orders & Design: starbucks@daltile.com

SIZE

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	15.20	4
	8" Hexagon Floor Tile	7-13/16" x 9-1/16" (19.95 cm X 23.04 cm)	5/16"	9.37	25

TRIM

	Type	Number	Size	Pieces/ Carton
	Cove Base	P36C9TB	6 x 12	12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Exterior Applications, pool decking, & other wet areas with minimal footwear	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

DAL-TILE 1-YEAR LIMITED WARRANTY (EXTENDED WARRANTIES AVAILABLE)

Dal-Tile Corporation warrants that manufactured products will be free from defect for a period of one-year from date of purchase. Defect is defined as a shortfall in the product to perform to Dal-Tile specifications as disclosed in product literature, within industry allowable tolerances as set forth in standard, national industry protocols. Dal-Tile provides detailed information in its product literature regarding appropriate tile and stone applications. Failure to comply with recommended applications voids this warranty. **THIS ONE-YEAR EXPRESS WARRANTY IS THE SOLE WARRANTY EXTENDED AND REPLACES ANY STATUTORY WARRANTIES TO THE MAXIMUM EXTENT ALLOWABLE BY LAW.** For full warranty information including implications, exclusions and limitations please visit www.Daltile.com.

THE INFORMATION RELEASED IS A PROPOSAL FOR CLIENT CONSIDERATION PURPOSES ONLY. FINAL TEST RESULTS & PART NUMBERS WILL BE PROVIDED

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%). 8" Hexagon: 3/16"	Medium (V2)

Additional installation recommendations can be found in the current edition TCNA Handbook and/or NTCA Reference Manual

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

CARE AND MAINTENANCE

Please refer to the "DalTile Care and Maintenance Guide" available at www.Daltile.com