

LA CREMA NU03

Please note: Image above displays the graphic design for the custom tile detailed in this document. Samples of actual material are available upon request.

WALL

**NU_TEMPO™
GLASS**

STARBUCKS CUSTOM ITEM DESCRIPTION

Color	NU03 La Crema
UOM	Square Foot


CONTACT INFORMATION

Orders & Design: starbucks@daltile.com

SIZE

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
 3/4" Glass Penny Round Mosaic 12-5/16" x 11-1/2" Sheet (31.30 cm x 29.00 cm Sheet)	1/4"	10.74	11

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Low (V1)

Additional installation recommendations can be found in the current edition TCNA Handbook and/or NTCA Reference Manual

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Exterior Applications, pool decking, & other wet areas with minimal footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Mosaics suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

CARE AND MAINTENANCE

Please refer to the "Daltile Care and Maintenance Guide" available at www.Daltile.com

DAL-TILE 1-YEAR LIMITED WARRANTY (EXTENDED WARRANTIES AVAILABLE)

Dal-Tile Corporation warrants that manufactured products will be free from defect for a period of one-year from date of purchase. Defect is defined as a shortfall in the product to perform to Dal-Tile specifications as disclosed in product literature, within industry allowable tolerances as set forth in standard, national industry protocols. Dal-Tile provides detailed information in its product literature regarding appropriate tile and stone applications. Failure to comply with recommended applications voids this warranty. THIS ONE-YEAR EXPRESS WARRANTY IS THE SOLE WARRANTY EXTENDED AND REPLACES ANY STATUTORY WARRANTIES TO THE MAXIMUM EXTENT ALLOWABLE BY LAW. For full warranty information including implications, exclusions and limitations please visit www.Daltile.com.

**THE INFORMATION RELEASED IS A PROPOSAL FOR CLIENT CONSIDERATION PURPOSES ONLY.
FINAL TEST RESULTS & PART NUMBERS WILL BE PROVIDED**