

DARE TO BE BOLD



ALTERATIONS™

GLAZED PORCELAIN
REVEAL IMAGING®

MARAZZI 
DARE TO BE BOLD™



ALTERATIONS™



DARK WEAVE AND LINEN

ALTERATIONS™ is an authentic fabric-look tailored to design fashionable spaces. Illustrative graphics reveal vivid visuals of interlacing rich fibers woven to perfection. The contemporary textile appeal is embedded on a durable porcelain floor tile and mosaic. Colors are extended to five on-trend shades for a fashion-forward design.

DARK WEAVE AND LINEN



LIGHT THREAD AND COTTON



ALTERATIONS™

GLAZED PORCELAIN

REVEAL IMAGING®

FLOOR TILE



AT61 Cotton



AT62 Linen



AT63 Light Thread




AT64 Woven Slate




AT65 Dark Weave

1 x 3 STACKED MOSAIC 12 x 12 SHEET




AT61 Cotton



AT62 Linen



AT63 Light Thread



AT64 Woven Slate



AT65 Dark Weave

USAGE



Floors	Walls	Countertops
F	W	C

ALTERATIONS™

GLAZED PORCELAIN

REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile	(11-13/16" x 23-7/16") (30.00 cm x 60.48 cm)	3/8"	15.6	8
	1 x 3 Stacked Mosaic (Mesh-mounted)	(11-7/8" x 11-7/8") (30.18 cm x 30.18 cm)	3/8"	9.8	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*


A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest®, visit marazzitile.com/DCOF.

APPLICATION NOTES:


Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

*Mosaic tile only

TRIM

Description	Number	Size	Shape
Floor Bullnose	P-43F9	3 x 24	

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) Mosaic: 1/8"	 Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmations should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.



7834 C.F. Hawn Freeway
Dallas, Texas 75217

www.marazzitile.com
contact@marazzitile.com

©2018 Marazzi | 01.18 | MZBRO113 Alterations™ Brochure

COVER FEATURES ALTERATIONS™ IN COTTON AND LIGHT THREAD

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with Marazzi Customer Service for details.