

# ALTERATIONS™

## GLAZED PORCELAIN

REVEAL IMAGING™

# MARAZZI

DARE TO BE BOLD™

### FLOOR TILE



**AT61** Cotton



**AT62** Linen



**AT63** Light Thread




**AT64** Woven Slate




**AT65** Dark Weave


### 1 x 3 MOSAIC 12 x 12 SHEET




**AT61** Cotton



**AT62** Linen



**AT63** Light Thread



**AT64** Woven Slate





**AT65** Dark Weave

### USAGE

Floors	Walls	Countertops
F	W	C

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile	(11-13/16" x 23-7/16") (30.00 cm x 60.48 cm)	3/8"	15.6	8
	1 x 3 Stacked Mosaic (Mesh-mounted)	(11-7/8" x 11-7/8") (30.18 cm x 30.18 cm)	3/8"	9.8	10

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*


A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](http://marazzitile.com/DCOF).

### APPLICATION NOTES:


Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

\*Mosaic tile only

## TRIM

Description	Number	Size	Shape
Floor Bullnose	P-43F9	3 x 24	

## INSTALLATION

Grout Joint Recommendation	Shade Variation
<b>Floor Tile:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)  <b>Mosaic:</b> 1/8"	 Medium Variation

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](http://marazzitile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmations should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors)

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.



Floor Tile



Wall Tile



Reveal Imaging™



Pre-Consumer  
Recycled Content

made in the  
**USA**



CERTIFIED  
**PORECELAIN**  
TILE  
0.4% or less water absorption

All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).