ARTISTIC REFLECTIONSTM GLAZED CERAMIC WALL AND MOSAICS







RTISTIC REFLECTIONS™

GLAZED CERAMIC WALL AND MOSAICS



FINISHES: MATTE | GLOSSY



























NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

2 X 20 WALL - GLOSSY / MATTE FINISH

AE04 Artic / AE05 Matte Artic



AE06 Mist / AE07 Matte Mist



AE08 Rain / AE09 Matte Rain



AE10 Onyx / AE11 Matte Onyx



AE12 Wave



AE13 Rose



AE14 Haze



AE15 Twighlight

2 X 10 WALL - GLOSSY / MATTE FINISH



AE04 Artic / AE05 Matte Artic



AE06 Mist / AE07 Matte Mist



AE08 Rain / AE09 Matte Rain



AE10 Onyx / AE11 Matte Onyx



AE12 Wave



AE13 Rose



AE14 Haze



AE15 Twighlight

3" HEXAGON MOSAIC - GLOSSY / MATTE FINISH 14 x 12 SHEET



AE04 Artic AE05 Matte Artic AE07 Matte Mist AE09 Matte Rain AE11 Matte Onyx

AE06 Mist



AE08 Rain



AE10 Onyx



AE12 Wave AE13 Rose



AE14 Haze



AE15 Twighlight













ARTISTIC REFLECTIONS

MATERIAL

 C_{G}

GLAZED CERAMIC WALL AND MOSAICS

MARAZZI A DARE TO BE BOLD

FINISHES: MATTE | GLOSSY

























WALL

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
2 x 20 Wall Tile	1-7/8" x 19-9/16" (4.90 cm x 49.80 cm)	3/8"	5.24	20
2 x 10 Wall Tile	1-7/8" x 9-13/16" (4.90 cm x 24.87 cm)	5/16"	5.24	40
3" Hexagon Mosaic (Mesh-mounted)	11-13/16" x 14-3/16" Sheet (30.10 cm x 36.10 cm Sheet)	5/16"	9.00	9

TRIM

Description	Number	Size	Shape	
Jolly	S1/210J	1/2 x 10		

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	*
Wet & Level - Interior Floor	≥ 0.42	*
Shower Floors (Residential or Light Commercial)	≥ 0.42	*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	*
Pool Linings	N/A	**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

- * Matte mosaics only.
- ** Mosaic tile only.

INSTALLATION

Wall Tile: 1/16"	Grout Joint Recommendation	Shade Variation
	Wall Tile: 1/16"	Low Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result	Mosaic Result (Matte)	Mosaic Result (Glossy)
Water Absorption	C373	< 20%	< 20%	< 20%
Breaking Strength	C648	120-130 lbs	> 275 lbs	> 275 lbs
Scratch Hardness	MOHS	4.0 - 6.0	8.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES



PRE-CONSUMER RECYCLED MATERIALS



REVEAL IMAGING®



All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com