

**BELLA VISTA™**  
GLAZED PORCELAIN FLOOR AND CERAMIC MOSAIC

**MARAZZI®**  
DARE TO BE BOLD™

STONE LOOK





# BELLA VISTA™

Discover the enchantment of Bella Vista™. Possessing the look of a blended limestone, Bella Vista™ delivers a transitional design to any space. Take your space to the mesmerizing Italian countryside with majestic views of natural beauty with this classic look, offering strong variation and dramatic movement. Popular 12 x 24 size and a modern color palette combine for a contemporary essence; add an octagon & dot mosaic for a truly unique design.



COVER PHOTO: IVORY  
ABOVE PHOTO: SMOKE

STONE LOOK



FINISHES: MATTE

<b>USAGE</b>  FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR	<b>MATERIAL</b>  PG  CG	<b>PRICING</b>  LOW HIGH	<b>SPECIAL FEATURES</b>  STEPWISE™  TRUEDGE™  MADE IN THE U.S.A.  LARGE FORMAT  MOSAIC/DECO  ENCAUSTIC  TERRAZZO  PAVER  CUSTOMIZE
--	---	--	--

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

## GLAZED PORCELAIN FLOOR TILE




**BV30** Ivory




**BV33** Smoke

## GLAZED CERAMIC 2" OCTAGON WITH 1" DOT MOSAIC



**BV30** Ivory



**BV33** Smoke



FINISHES: MATTE



STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile	11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)	5/16"	17.37	9
	2" Octagon with 1" Dot Mosaic (Dot-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	10.00	10

## TRIM

Description	Number	Size	Shape
Floor Bullnose	P43C9	3 x 12	

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](https://marazzitile.com/DCOF).

### APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

\* Mosaic tile only

## INSTALLATION

Grout Joint Recommendation	Shade Variation
<b>Floor Tile:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) <b>Mosaic:</b> 1/8"	Random Variation

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](https://marazzitile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](https://marazzitile.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](https://marazzitile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [marazzitile.com](https://marazzitile.com).

## FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](https://marazzitile.com).