



Random Mosaic 12"x12"

Random Mosaic 12"x12" Because stained glass in translucent by nature light will penetrate through it prior to installation, making the uninstalled sheet appear to be lighter than the grouted sample boards. Once the stained glass tile has been installed it will appear darker and opaque
 Install tile per manufacturer's instruction and industry standards.

359 Clay Road www.marazzitile.com Sunnyvale, Texas 75182 contact@marazzitile.com

American Marazzi Tile, Inc. Telephone Headquarters & 972.226.0110 Manufacturing Plant Fax 972.226.5629

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.

CATWALK is available nationwide. To locate your nearest Distributor call American Marazzi Tile Customer Service or visit www.marazzitile.com



UJ9V Olive Oxfords Random Mosaic 12"x12"

Random Mosaic 12"x12"

- To avoid adversely affecting the color of glass tile, white thin-set is required for all installations.
 Glass tile must have a minimum 1/16" grout joint and should not be butt set.
 Use latex additive in the white thin-set to ensure adequate performance.
- Ose rates additioned in the writte trim-set to ensure adequate performance.
 Wipe back of the tile and substrate clean with a clean damp sponge. This will help achieve 100% mortar coverage.
 To ensure adequate coverage and full contact to the tile, it is recommended to lightly back butter the tile.
 Tile shall set for 24 hours before grouting.
 Due to the impervious quality of glass, the grout will take longer to begin setting.
 Use a damp sponge only for the final washing and smoothing of the grout joints.

Use a glass cleaner and a soft lint free cloth for cleaning glass tile. To remove soap scum or water deposits a minimally abrasive cleanser and soft bristle brush can be used.

No acids should be used for cleaning grout haze.

APPLICATIONSCatwalk can be installed in interior and exterior areas.


Catwalk is suitable for walls, swimming pools, fountains and showers.

MINE	Sizes	Pcs	Weight (lbs.)	Thickness	
om Mosaic	12"x 12"	10	13	0.118	





















MARAZZI Susa

A Collection of Glass Mosaics