







CRYSTAL STONE IITM







































MARAZZI


DARE TO BE BOLD

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE STONE USAGE GUIDE FOR FULL PRODUCT DETAILS.

LINEAR GLASS/STONE MOSAIC 12 x 12 SHEET



UL94 Pearl



UL95 Pewter



UL93 Terracotta



UL8Z Espresso



UL92 Slate

TAL STO GLASS/STONE MOSAICS



FINISHES: POLISHED | HONED





























NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE STONE USAGE GUIDE FOR FULL PRODUCT DETAILS.

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
Linear Mosaic (Mesh-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	5/16"	5.81	6

INSTALLATION

Grout Joint Recommendation	Shade Variation		
Mosaic: 1/8"	Random Variation		

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Mosaic Result		
Water Absorption	C373	< 0.5%		
Breaking Strength	C648	> 100 lbs		
Scratch Hardness	MOHS	4.0		
Chemical Resistance	C650	Resistant		

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Use of a white latex modified thin-set is recommended for installation.

FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com $\,$