

MODERN OASIS™
GLAZED PORCELAIN AND CERAMIC MOSAICS

MARAZZI®
DARE TO BE BOLD™

STONE LOOK



MODERN OASIS™

Monochromatic shadings and texture resembling windswept sand dunes define the contemporary limestone vibe of MODERN OASIS™. Rich, realistic graphic variations – linear to swirl – effortlessly flow from piece to piece in calming, organic shades. Dual-sized porcelain planks with flat surfaces, clean, straight edges and a controlled, neutral palette juxtapose strikingly with bolder elements of wood, glass and stone.



COVER PHOTO: STORMY SKY
ABOVE PHOTO: SOFT CLOUD

STONE LOOK

FINISHES: MATTE

| | | | | | | | | | | | | | | | | | |
|--|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| USAGE | | MATERIAL | | PRICING | SPECIAL FEATURES | | | | | | | | | | | | |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| FLOOR | WALL | COUNTERTOP | SHOWER FLOOR | EXTERIOR FLOOR | PG | C | LOW | HIGH | STEPWISE™ | TRUEEDGE™ | MADE IN THE U.S.A. | LARGE FORMAT | MOSAIC/DECO | ENCAUSTIC | TERRAZZO | PAVER | CUSTOMIZE |

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK


12 x 24 FLOOR TILE



MD05 Soft Cloud



MD06 Morning Haze



MD08 Gentle Rain



MD09 Stormy Sky

24 x 24 FLOOR TILE



MD05 Soft Cloud



MD06 Morning Haze




MD08 Gentle Rain



MD09 Stormy Sky


1 x 3 STACKED MOSAIC 12 x 12 SHEET



MD05 Soft Cloud



MD06 Morning Haze




MD08 Gentle Rain



MD09 Stormy Sky


2 x 2 MOSAIC 12 x 12 SHEET



MD05 Soft Cloud



MD06 Morning Haze



MD08 Gentle Rain



MD09 Stormy Sky



VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE

FLOOR

WALL

COUNTERTOP

SHOWER FLOOR

EXTERIOR FLOOR

MATERIAL

PG
GLAZED
PORCELAIN

C
CERAMIC

PRICING

LOW

HIGH

SPECIAL FEATURES

STEPWISE™

TRUEEDGE™

MADE IN THE U.S.A.

LARGE FORMAT

MOSAIC/DECO

ENCAUSTIC

TERRAZZO





PAVER

CUSTOMIZE

STONE LOOK




NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

| | | | Thickness | Sq. Ft./ Carton | Pieces/ Carton |
|--|--|--|-----------|--------------------|-------------------|
|  | 24 x 24 Floor Tile | 23-13/16" x 23-13/16" (60.48 cm x 60.48 cm) | 5/16" | 15.76 | 4 |
|  | 12 x 24 Floor Tile | 11-13/16" x 23-13/16" (30.00 cm x 60.48 cm) | 5/16" | 17.60 | 9 |
|  | 1 x 3 * Stacked Mosaic (Dot-mounted) | 12-1/8" x 12-1/8" Sheet (30.80 cm x 30.80 cm) | 1/4" | 10.20 | 10 |
|  | 2 x 2 * Square Mosaic (Dot-mounted) | 12" x 12" Sheet (30.48 cm x 30.48 cm) | 1/4" | 10.00 | 10 |







*Ceramic Body

TRIM

| Description | Number | Size | Shape |
|---------------------|--------|--------|---|
| Floor Bullnose | P43C9 | 3 x 12 |  |
| Cove Base | P36C9 | 6 x 12 |  |
| Cove Base Outcorner | PC36C9 | 6 x 1 |  |

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

APPLICATIONS

| | Target DCOF wet | Suitable |
|--|--------------------|---|
| Dry & Level – Interior Floor | N/A |  |
| Wet & Level – Interior Floor | ≥ 0.42 |  |
| Shower Floors - Standard Center Drain (Residential or Light Commercial) | ≥ 0.42 |  * |
| Shower Floors - Linear drain | | |
| Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear) | ≥ 0.60 | |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A |  |
| Countertops | N/A |  |
| Pool Linings | N/A |  * |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.


APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.

INSTALLATION

| Grout Joint Recommendation | Shade Variation |
|--|--|
| Floor Tile: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.) |  Medium Variation |
| Mosaic: 1/8" | |

PERFORMANCE CHARACTERISTICS

| | ASTM# | Floor Result | Mosaic Result |
|---------------------|-------|-----------------|------------------|
| Water Absorption | C373 | < 0.5% | < 3.0% |
| Breaking Strength | C648 | > 275 lbs | > 250 lbs |
| Scratch Hardness | MOHS | 8.0 | 8.0 |
| Chemical Resistance | C650 | Resistant | Resistant |

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

| | | | |
|---|-----------------------|---|------------------------------------|
| 1 | Residential Bathrooms | 3 | All Residential / Light Commercial |
| 2 | All Residential Areas | ④ | All Residential / Commercial |

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazziusa.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazziusa.com.

FEATURES

 POST-CONSUMER RECYCLED MATERIALS

 PRE-CONSUMER RECYCLED MATERIALS

 MADE IN THE U.S.A.

 REVEAL IMAGING®

 CERTIFIED PORCELAIN
90% or less water absorption

 ZERO TO X
Healthy Homes | Healthy Planet

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.