

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WOOD LOOK

**COLORBODY™ PORCELAIN FLOOR TILE**



**PR24** Distressed Oak



**PR26** Petrified Gray



VISIT [MARAZZIUSA.COM/WHYTILE](http://MARAZZIUSA.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WOOD LOOK

**SIZES**

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	9 x 36 Floor Tile	8-13/16" x 35-1/4" (22.50 cm x 89.50 cm)	3/8"	13.02	6
	6 x 36 Floor Tile	5-13/16" x 35-1/4" (14.80 cm x 89.50 cm)	3/8"	12.78	9

**TRIM**

Description	Number	Size	Shape
Floor Bullnose	P-43F9	3 x 24	
Cove Base	P-36C9TB	6 x 12	
Cove Base Outcorner	PC-36C9TB	6 x 1	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position. Cove base and cove corner trim are suitable for non-freezing climates only.

**APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazziusa.com/DCOF](http://marazziusa.com/DCOF).

**APPLICATION NOTES:**

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

**INSTALLATION**

Grout Joint Recommendation	Shade Variation
Floor: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%)	High Variation

**PERFORMANCE CHARACTERISTICS**

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [marazziusa.com/information/TestResults](http://marazziusa.com/information/TestResults).

**DURABILITY**

**Floor Surface Wear Resistance**

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

**NOTES**

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

**FEATURES**



REVEAL IMAGING®



CERTIFIED PORCELAIN™  
TILE  
100% in good color throughout

ZEROTOX®  
Healthy Homes Healthy Planet

All or select items within this series meet the requirements for these qualifications. For more information visit [marazziusa.com](http://marazziusa.com).