



MONOCHROMATIC LOOK



RHYME AND REASON[™]

There's a rhyme and reason to this playfully poetic wall tile. Each piece features a unique textured surface, creating bold patterns that add depth and interest into your design. Curate a modern atmosphere with the clever color palette and endless installation options; Rhyme and Reason was designed with the trendsetter in mind.

COVER PHOTO: WARM TERRACOTTA ABOVE PHOTO: INDIGO

MONOCHROMATIC LOOK

VIIII

RHYME AND REASON TM GLAZED CERAMIC FINISHES: MATTE	MARAZZI
USAGE US	
NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.	4 x 5 HEX WALL TILE - RANDOM ASSORTMENT
RR16 Bone	RR16 Bone
RR17 Canvas	RR17 Canvas
	RR18 Indigo
RR18 Indigo	
	RR19 Artichoke
RR19 Artichoke	
	RR20 Warm Terracotta

RR20 Warm Terracotta

NOTE: 6 x 6 includes five unique structures that are pre-boxed in a random assortment. Individual designs are not sold separately. NOTE: 4 x 5 Hex includes four unique structures that are pre-boxed in a random assortment. Individual designs are not sold separately.



RHYME AND REASONTM

FINISHES: MATTE

USAGE



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 6 Wall Tile	6" x 6" (15.31 cm x 15.31 cm)	1/4" (7.75mm)	12.60	50
\bigcirc	4 x 5 Hex Wall Tile	4-1/4" x 4-15/16" (10.88 cm x 12.57 cm)	1/4" (7.75mm)	3.33	30

* 6 x 6 Wall Tile is made in the U.S.A

TRIM

Description	Number	Size	Shape
Jolly (4 pieces per card)	S1/212J	1/2 x 12	

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTestTM, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16"	Low Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Results
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120 - 230 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: marazziusa. com/Factors.

<u>**</u>=

FEATURES



MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.



DARE TO BE BOLD

MONOCHROMATIC COLOR