

TREVERKSOUL™  
GLAZED PORCELAIN

MARAZZI®  
DARE TO BE BOLD™

WOOD LOOK



# TREVERKSOUL™

Presenting an aristocratic soul and a contemporary feel, Treverksoul™ mimics realistic hardwood visuals combined with authentic knot and grainline variations. Inspired by antique parquet floors, this collection revives a style from the past and brings a refreshed ambiance into your space with its distinct chevron shape—coupled with rich variation in color and shade.



COVER PHOTO: NEUTRAL  
ABOVE PHOTO: GREY

WOOD LOOK

# TREVERKSOUL™

Presenting an aristocratic soul with a contemporary feel, Treverksoul™ mimics realistic hardwood visuals combined with authentic knot and grainline variations. Inspired by antique parquet floors, this collection attractively revives a style from the past. Its distinct chevron shape filled with rich color and shade variation brings a refreshed ambiance to any space.



COVER PHOTO: NEUTRAL  
ABOVE PHOTO: GREY

WOOD LOOK

# TREVERKSOUL™

GLAZED PORCELAIN

# MARAZZI®

DARE TO BE BOLD™

FINISHES: MATTE

### USAGE



### MATERIAL



### PRICING



### SPECIAL FEATURES



WOOD LOOK

## FLOOR TILE



TR60 Neutral



TR61 Brown



TR62 Grey



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



SIMPLICLEAN™

VISIT [MARAZZITILE.COM/WHYTILE](http://MARAZZITILE.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

<b>USAGE</b>			<b>MATERIAL</b>		<b>PRICING</b>		<b>SPECIAL FEATURES</b>						
FLOOR	WALL	COUNTERTOP	PG	LOW HIGH	STEPWISE	TRUEDGE	MADE IN THE U.S.A.	LARGE FORMAT	MOSAIC/DECO	ENCAUSTIC	TERRAZZO	PAVER	CUSTOMIZE

WOOD LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 21 Floor Tile	4-5/16" x 21-1/4" (11.00 cm x 54.00 cm)	3/8"	10.12	18

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](http://marazzitile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
<b>Floor Tile:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	Random Variation

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](http://marazzitile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [marazzitile.com](http://marazzitile.com).

## FEATURES

	PRE-CONSUMER RECYCLED MATERIALS		REVEAL IMAGING®
	CERTIFIED PORCELAIN		ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).