



American Marazzi Tile, Inc.
Headquarters & Manufacturing Plant

359 Clay Road
Sunnyvale, Texas 75182

Telephone
972.226.0110
Fax
972.226.5629

www.marazzitile.com
contact@marazzitile.com

Walnut Canyon is available nationwide.
To locate your nearest Distributor call
American Marazzi Tile Customer Service
or visit www.marazzitile.com

DISTRIBUTED BY:

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.



Walnut Canyon

color body porcelain tile

Walnut Canyon

A fresh take on the limestone used by early Southwestern cliff dwellers, WALNUT CANYON combines the strength of color body porcelain with the natural beauty of native stone in all its randomly varied faces for today's floors and walls. Gently puddled ranges of warm, soothing, matte colors wash across the subtle concavities and indentations that define the line.

Re-invent classic or modern, residential or commercial venues with the broad range of colors, sizes, mosaics and trims offered. Balance large formats with square or rectangular mosaics; create intriguing patterns with correlating modulars; finish commercial areas with sanitary covebase and angles. Accessorize with various glass, metal, fabric or wood embellishments to further personalize and expand the design possibilities of this durable, easy-to-clean, healthy flooring choice that's ADA-compliant.



GOLDEN

Floor: 20"x20" Backsplash: 6½"x6½" - 2"x2" Mosaic Square - 2"x4" Mosaic Brick - 2"x13" Bronze Chair Rail - ½"x13" Bronze Pencil Liner - 2"x2" Bronze Floral Insert

UMBER

Floor: 13"x13"



Dramatic tonal ranges of rustic travertine tempt the eyes to dance across surfaces that continually transform, depending on light and shadow present in the area. A leaf-filtered patio, a sunny family kitchen, a candle-lit restaurant . . . ever-changing, ever-fresh environments.



MULTI

Floor: 20"x20" - 3"x13" Bullnose





CREAM

Floor: 13"x13" Bathtub: 6½"x6½" - 2"x2" Mosaic Square -
2"x4" Mosaic Brick - 2"x2" Bronze Floral Insert -
½"x13" Bronze Pencil Liner - 2"x13" Bronze Chair Rail
Wall: 2"x4" Mosaic Brick - 3"x13" Bullnose

Walnut Canyon floor and wall tile - color body porcelain stoneware



Cream



UJ3V Cream
20"x20"



UJ3U Cream
13"x13"



UJ3W Cream
6 1/2"x6 1/2"

Decos



UJ34 Cream
Mosaic - Square 2"x2"
13"x13"



UJ35 Cream
Mosaic - Brick 2"x4"
13"x13"



UJ6U Nickel
Floral Insert
4"x4"



UJ6W Nickel
Floral Insert
2"x2"



UJ6Y Nickel
Floral Insert
1"x1"

Trims



UJ3Y Cream
Bullnose
3"x13"



UJ3Z Cream
Sanitary Cove Base
6"x13"



UJ32 Cream
Sanitary Cove Base In Angle
1"x6"



UJ33 Cream
Sanitary Cove Base Out Angle
1"x6"



UJ6Q Nickel
Pencil Liner
1/2"x13"



UJ6N Nickel
Chair Rail
2"x13"

ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 429 lbf.	C648
Facial Dimension	-3.0% < Nominal ≤ 3.0%	Within Standard	C499
Nominal Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (squareness)	+/- 0.50% or +/- 2.0mm**	Within Standard	C502
Warpage (flatness)	+/- 0.75% or +/- 2.3mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV*	C1027
Dry Coefficient of Friction	As Reported	0.70 ≤ C.O.F. < 0.80	C1028
Wet Coefficient of Friction	As Reported	0.60 ≤ C.O.F. < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Abrasion Resistance / Suggested Applications

Class IV: tile in this class may withstand heavier amounts of traffic with greater amounts of dirt and/or other abrasives present including commercial kitchens and areas with regular traffic from the outside. See Coefficient of Friction and Frost Resistance for installation-specific details.

** Whichever is less



Floor Tile



Recycled Content Minimum 21%



Wall Tile



Trim Available



Abrasion Resistance



Frost Resistant



C.O.F. (Wet)



Meets ADA Recommendations



C.O.F. (Dry)



Spec Wizard



Modular Tile



Decorative Tile



Contributes to
LEED Credits



Substantial Variation



Goden



UHC6 Golden
20"x20"



UHC3 Golden
13"x13"



UHDQ Golden
6 1/2"x6 1/2"

Decos



UHD4 Golden
Mosaic - Square 2"x2"
13"x13"



UHD7 Golden
Mosaic - Brick 2"x4"
13"x13"



UJ6V Bronze
Floral Insert
4"x4"



UJ6X Bronze
Floral Insert
2"x2"



UJ6Z Bronze
Floral Insert
1"x1"

Trims



UHDW Golden
Bullnose
3"x13"



UHDZ Golden
Sanitary Cove Base
6"x13"



UJ2B Golden
Sanitary Cove Base In Angle
1"x6"



UJ2E Golden
Sanitary Cove Base Out Angle
1"x6"



UJ6R Bronze
Pencil Liner
1/2"x13"



UJ6P Bronze
Chair Rail
2"x13"

	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Modular Tile	6 1/2" x 6 1/2"	36	10.55	42	0.335
Modular Tile	13" x 13"	15	17.90	73	0.335
Field Tile	20" x 20"	6	16.15	84	0.433
Mosaic - Square 2"x2"	13" x 13"	10		39	Compatible
Mosaic - Brick 2"x4"	13" x 13"	10		45	Compatible
Insert	4" x 4"	15		7	Compatible
Insert	2" x 2"	60		13	Compatible
Insert	1" x 1"	125		14	Compatible
Pencil Liner	1/2" x 13"	50		17	Compatible
Chair Rail	2" x 13"	20		5	Compatible
Cove Base	6" x 13"	12		42	Compatible
Cove Base In Angle	1" x 6"	6		2	Compatible
Cove Base Out Angle	1" x 6"	6		2	Compatible
Bullnose	3" x 13"	20		21	Compatible

	Sizes	Ctn	Sq. Ft.	Weight (lbs.)
Modular Tile	6 1/2" x 6 1/2"	51	538.05	2131
Modular Tile	13" x 13"	38	680.20	2774
Field Tile	20" x 20"	24	387.60	2016

Walnut Canyon floor and wall tile - color body porcelain stoneware



Multi



UHC7 Multi
20"x20"



UHC4 Multi
13"x13"



UHDR Multi
6½"x6½"

Decos



UHD5 Multi
Mosaic - Square 2"x2"
13"x13"



UHD8 Multi
Mosaic - Brick 2"x4"
13"x13"



UJ6U Nickel
Floral Insert
4"x4"



UJ6W Nickel
Floral Insert
2"x2"



UJ6Y Nickel
Floral Insert
1"x1"

Trims



UHDX Multi
Bullnose
3"x13"



UHD2 Multi
Sanitary Cove Base
6"x13"



UJ2C Multi
Sanitary Cove Base In Angle
1"x6"



UJ2F Multi
Sanitary Cove Base Out Angle
1"x6"



UJ6Q Nickel
Pencil Liner
½"x13"



UJ6N Nickel
Chair Rail
2"x13"

ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 429 lbf.	C648
Facial Dimension	-3.0% < Nominal ≤ 3.0%	Within Standard	C499
Nominal Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (squareness)	+/- 0.50% or +/- 2.0mm**	Within Standard	C502
Warpage (flatness)	+/- 0.75% or +/- 2.3mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV*	C1027
Dry Coefficient of Friction	As Reported	0.70 ≤ C.O.F. < 0.80	C1028
Wet Coefficient of Friction	As Reported	0.60 ≤ C.O.F. < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Abrasion Resistance / Suggested Applications

Class IV: tile in this class may withstand heavier amounts of traffic with greater amounts of dirt and/or other abrasives present including commercial kitchens and areas with regular traffic from the outside. See Coefficient of Friction and Frost Resistance for installation-specific details.

** Whichever is less



Floor Tile



Wall Tile



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



Modular Tile



Decorative Tile



Substantial Variation



Recycled Content Minimum 21%



Trim Available



Frost Resistant



Meets ADA Recommendations



Spec Wizard



Contributes to
LEED Credits



Umber



UHC5 Umber
20"x20"



UHC2 Umber
13"x13"



UHDP Umber
6 1/2"x6 1/2"

Decos



UHD3 Umber
Mosaic - Square 2"x2"
13"x13"



UHD6 Umber
Mosaic - Brick 2"x4"
13"x13"



UJ6V Bronze
Floral Insert
4"x4"



UJ6X Bronze
Floral Insert
2"x2"



UJ6Z Bronze
Floral Insert
1"x1"

Trims



UHDV Umber
Bullnose
3"x13"



UHDY Umber
Sanitary Cove Base
6"x13"



UJ2A Umber
Sanitary Cove Base In Angle
1"x6"



UJ2D Umber
Sanitary Cove Base Out Angle
1"x6"



UJ6R Bronze
Pencil Liner
1/2"x13"



UJ6P Bronze
Chair Rail
2"x13"

	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Modular Tile	6 1/2" x 6 1/2"	36	10.55	42	0.335
Modular Tile	13" x 13"	15	17.90	73	0.335
Field Tile	20" x 20"	6	16.15	84	0.433
Mosaic - Square 2"x2"	13" x 13"	10		39	Compatible
Mosaic - Brick 2"x4"	13" x 13"	10		45	Compatible
Insert	4" x 4"	15		7	Compatible
Insert	2" x 2"	60		13	Compatible
Insert	1" x 1"	125		14	Compatible
Pencil Liner	1/2" x 13"	50		17	Compatible
Chair Rail	2" x 13"	20		5	Compatible
Cove Base	6" x 13"	12		42	Compatible
Cove Base In Angle	1" x 6"	6		2	Compatible
Cove Base Out Angle	1" x 6"	6		2	Compatible
Bullnose	3" x 13"	20		21	Compatible

	Sizes	Ctn	Sq. Ft.	Weight (lbs.)
Modular Tile	6 1/2" x 6 1/2"	51	538.05	2131
Modular Tile	13" x 13"	38	680.20	2774
Field Tile	20" x 20"	24	387.60	2016